## **ATEN**

## ATEN CL5708IN-ATA-2XK06RG KVM-kytkin Telineasennus musta

Tuotemerkki: ATEN Tuotekoodi: CL5708IN-ATA-2XK06RG

Tuotteen nimi: CL5708IN-ATA-2XK06RG

ATEN CL5708IN-ATA-2XK06RG. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. Tietoturva-algoritmit: 128-bit RC4, RSA, SSL/TLS. HD-tyyppi: WUXGA, Enimmäiserottelutarkkuus: 1920 x 1200 pikseliä, Skannausväli: 1,255 s. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli, Muovi. Näyttö: LCD, Näytön halkaisija: 48,3 cm (19")





| Ports & interfaces   |                                    | Display   |  |
|--|------------------------------------|---|--|
| Number of computers controlled * Keyboard port type * Mouse port type * Video port type *                    | 8<br>USB, PS/2<br>USB, PS/2<br>VGA | Built-in display * Display Display diagonal On Screen Display (OSD)                     | ✓<br>LCD<br>48.3 cm (19")<br>✓         |
| Console ports * Console USB ports quantity   | RJ-45, USB A, VGA (D-Sub)<br>1     | Power   |  |
| USB connector type   | USB Type-A                         | Power source  | AC                                     |
| Network Ethernet LAN (RJ-45) ports Security algorithms   | 1<br>128-bit RC4, RSA, SSL/TLS     | Input voltage AC input frequency Input current  | 100-240 V<br>50 - 60 Hz<br>1 A         |
| Performance  | 120-bit NC4, N3A, 33L/1L3          | System requirements   |  |
| HD type * Maximum resolution *   | WUXGA<br>1920 x 1200 pixels        | Windows operating systems supported   | <b>/</b>                               |
| Scan interval  | 1.255 s                            | Linux operating systems supported   | <b>✓</b>                               |
| DDC2B support  | ✓                                  | Mac operating systems supported   | <b>✓</b>                               |
| HDCP   | <b>✓</b>                           | Operational conditions  |  |
| Hot-Plug support<br>Daisy chain  | 1                                  | Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) | 0 - 50 °C<br>-20 - 60 °C<br>0 - 80%    |
| Power on detection   |                                    |   |  |
|  | •                                  | Weight & dimensions   |  |
| Firmware upgradeable  Design  Rack mounting *  Back capacity   | <b>*</b>                           | Weight & dimensions Width Depth Height Weight   | 689.2 mm<br>480 mm<br>44 mm<br>13.4 kg |
| Design   |                                    | Width<br>Depth<br>Height<br>Weight  | 480 mm<br>44 mm                        |
| Design  Rack mounting * Rack capacity  | ✓<br>1U                            | Width<br>Depth<br>Height  | 480 mm<br>44 mm<br>13.4 kg             |
| Design  Rack mounting *  Rack capacity  Product colour *   | ✓<br>1U<br>Black                   | Width Depth Height Weight Packaging content   | 480 mm<br>44 mm                        |
| Design  Rack mounting * Rack capacity Product colour * Housing material                                      | ✓<br>1U<br>Black<br>Metal, Plastic | Width Depth Height Weight  Packaging content Cables included                            | 480 mm<br>44 mm<br>13.4 kg             |
| Design  Rack mounting * Rack capacity Product colour * Housing material LED indicators                       | 1U<br>Black<br>Metal, Plastic      | Width Depth Height Weight  Packaging content Cables included Manual                     | 480 mm 44 mm 13.4 kg  AC, KVM          |
| Design  Rack mounting * Rack capacity Product colour * Housing material LED indicators Display switch button | 1U<br>Black<br>Metal, Plastic      | Width Depth Height Weight  Packaging content Cables included Manual                     | 480 mm 44 mm 13.4 kg  AC, KVM          |

