## **ATEN**

## ATEN CL5708IN-ATA-2XK07GG KVM-kytkin Telineasennus musta

Tuotemerkki: ATEN Tuotekoodi: CL5708IN-ATA-2XK07GG

Tuotteen nimi: CL5708IN-ATA-2XK07GG

ATEN CL5708IN-ATA-2XK07GG. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. Tietoturva-algoritmit: 128-bit RC4, RSA, SSL/TLS. HD-tyyppi: WUXGA, Enimmäiserottelutarkkuus: 1920 x 1200 pikseliä, Skannausväli: 1,255 s. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli, Muovi. Näyttö: LCD, Näytön halkaisija: 48,3 cm (19")





| Ports & interfaces   |  | Display   |  |
|--|--|---|--|
| Number of computers controlled * Keyboard port type * Mouse port type * Video port type * Console ports * Console USB ports quantity | 8<br>USB, PS/2<br>USB, PS/2<br>VGA<br>RJ-45, USB A, VGA (D-Sub)<br>1   | Built-in display * Display Display diagonal On Screen Display (OSD)                                   | ✓<br>LCD<br>48.3 cm (19")              |
|  |  | Power   |  |
| USB connector type   | USB Type-A   | Power source  | AC                                     |
| <b>Network</b><br>Ethernet LAN (RJ-45) ports   | 1  | Input voltage  AC input frequency Input current   | 100-240 V<br>50 - 60 Hz<br>1 A         |
| Security algorithms  | 128-bit RC4, RSA, SSL/TLS  | System requirements   |  |
| Performance  HD type *  Maximum resolution *  Scan interval  | Windows operating system supported  * WUXGA supported  Inux operating systems support  Inux operating systems support  Operational conditions  Support  Support  Operational conditions  Operating temperature (T-T  Storage temperature (T-T  Operating relative humidies  on detection  on detection | Windows operating systems supported Linux operating systems supported Mac operating systems supported | * * *                                  |
| DDC2B support  |  | Operational conditions  |  |
| HDCP Hot-Plug support Daisy chain  |  | Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)               | 0 - 50 °C<br>-20 - 60 °C<br>0 - 80%    |
| Power on detection   |  | Weight & dimensions   |  |
| Firmware upgradeable  Design  Rack mounting *  Rack capacity   |  | Depth<br>Height   | 689.2 mm<br>480 mm<br>44 mm<br>13.4 kg |
| Product colour *   | Black  | Packaging content   |  |
| Housing material<br>LED indicators<br>Display switch button<br>Push button   | Metal, Plastic   | Cables included<br>Manual<br>Rack mount kit   | AC, KVM<br>✓                           |
| Hot keys   | ✓<br>Curies  |   |  |
| Keyboard language  | Swiss  |   |  |

