



## ATEN CL5708M KVM switch Rack mounting Black

**Brand :** ATEN

**Product code:** CL5708M-ATA-2XK06SG

**Product name :** CL5708M

17" LED-backlit LCD KVM Switch

ATEN CL5708M KVM switch Rack mounting Black:

The CL5708 Slideaway™ LCD KVM Switch is a control unit that allows access to multiple computers from a single PS/2 or USB KVM (keyboard, video, and mouse) console. A single CL5708 can control up to 8 computers. As many as 31 additional KVM switches can be daisy-chained to the CL5708, so that up to 256 computers can all be controlled from a single KVM console.

The CL5708 offers a space-saving, streamlined approach to KVM switch technology by integrating a keyboard, 17" or 19" LED-backlit LCD monitor, and touchpad in a 1U rack-mountable sliding housing. ATEN CL5708M. Mouse port type: USB, USB connector type: USB Type-A. Maximum resolution: 1280 x 1024 pixels, Scan interval: 1,255 s. Product colour: Black, Rack capacity: 1U, Housing material: Metal, Plastic. Display: LCD, Display diagonal: 43.2 cm (17"). Input voltage: 100-240 V, AC input frequency: 50 - 60 Hz, Input current: 1 A



Ports & interfaces		Power	
Number of computers controlled *	8	Input current	1 A
Mouse port type *	USB	Power consumption (typical)	16 W
USB connector type	USB Type-A	<b>System requirements</b>	
Performance		Windows operating systems supported	✓
Maximum resolution *	1280 x 1024 pixels	Linux operating systems supported	✓
Scan interval	1,255 s	Mac operating systems supported	✓
DDC2B support	✓	<b>Operational conditions</b>	
Hot-swap	✓	Operating temperature (T-T)	0 - 40 °C
Design		Storage temperature (T-T)	-20 - 60 °C
Rack mounting *	✓	Operating relative humidity (H-H)	0 - 80%
Rack capacity	1U	<b>Weight &amp; dimensions</b>	
Product colour *	Black	Width	642.7 mm
Housing material	Metal, Plastic	Depth	480 mm
LED indicators	✓	Height	44 mm
<b>Display</b>		Weight	13.5 kg
Built-in display *	✓	<b>Packaging content</b>	
Display	LCD	Manual	✓
Display diagonal	43.2 cm (17")	<b>Logistics data</b>	
On Screen Display (OSD)	✓	Harmonized System (HS) code	85176200
Power			
Input voltage	100-240 V		
AC input frequency	50 - 60 Hz		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.