ATEN

ATEN CL5708M KVM switch Rack mounting Black

Brand: ATEN Product code: CL5708M-ATA-2XK06UG

Product name: CL5708M

17" LED-backlit LCD KVM Switch

ATEN CL5708M KVM switch Rack mounting Black:

The CL5708 Slideaway™ LCD KVM Switch is a control unit that allows access to multiple computers from a single PS/2 or USB KVM (keyboard, video, and mouse) console. A single CL5708 can control up to 8 computers. As many as 31 additional KVM switches can be daisy-chained to the CL5708, so that up to 256 computers can all be controlled from a single KVM console.

The CL5708 offers a space-saving, streamlined approach to KVM switch technology by integrating a keyboard, 17" or 19" LED-backlit LCD monitor, and touchpad in a 1U rack-mountable sliding housing. ATEN CL5708M. Mouse port type: USB, USB connector type: USB Type-A. Maximum resolution: 1280 x 1024 pixels, Scan interval: 1,255 s. Product colour: Black, Rack capacity: 1U, Housing material: Metal, Plastic. Display: LCD, Display diagonal: 43.2 cm (17"). Input voltage: 100-240 V, AC input frequency: 50 - 60 Hz, Input current: 1 A

50 - 60 Hz

AC input frequency





| Ports & interfaces | | Power | |
|----------------------------------|--------------------|-----------------------------------|-------------|
| Number of computers controlled * | 8 | Input current | 1 A |
| Mouse port type * | USB | Power consumption (typical) | 16 W |
| USB connector type | USB Type-A | System requirements | |
| Performance | | Windows operating systems | / |
| Maximum resolution * | 1280 x 1024 pixels | supported | |
| Scan interval | 1,255 s | Linux operating systems supported | • |
| DDC2B support | ✓ | Mac operating systems supported | ✓ |
| Hot-swap | ✓ | Operational conditions | |
| Design | | Operating temperature (T-T) | 0 - 40 °C |
| Rack mounting * | ✓ | Storage temperature (T-T) | -20 - 60 °C |
| Rack capacity | 1U | Operating relative humidity (H-H) | 0 - 80% |
| Product colour * | Black | Weight & dimensions | |
| Housing material | Metal, Plastic | Width | 642.7 mm |
| LED indicators | ✓ | Depth | 480 mm |
| Display | | Height | 44 mm |
| Built-in display * | 1 | Weight | 13.5 kg |
| Display | LCD | Packaging content | |
| Display diagonal | 43.2 cm (17") | Manual | ✓ |
| On Screen Display (OSD) | ✓ | Logistics data | |
| Power | | Harmonized System (HS) code | 85176200 |
| Input voltage | 100-240 V | | |

