

KYOCERA ECOSYS MA5500ifx Laser A4 1200 x 1200 DPI 55 ppm

Tuotemerkki : KYOCERA

Tuoteperhe: ECOSYS

Tuotekoodi: 110C0Z3NL0

Tuotteen nimi : MA5500ifx

KYOCERA ECOSYS MA5500ifx. Tulostustekniikka: Laser, Tulostus: Yksittäistulostus, Suurin resoluutio: 1200 x 1200 DPI. Kopiointi: Yksittäiskopiointi, Kopioinnin enimmäistarkkuus: 600 x 600 DPI. Skannaus: Väriskannaus, Optinen skannauserottelutarkkuus: 600 x 600 DPI. Faksaus: Yksittäisfaksin lähetyks. Kaksipuolinen toiminto: Kopiointi, Faksi, Tulosta, Skannaus. Suurin ISO A-luokan paperikoko: A4. Suoratulostus. Tuotteen väri: musta, Valkoinen



Printing		Input & output capacity	
Duplex printing mode	Auto	Maximum output capacity	500 sheets
Print technology *	Laser	Paper handling	
Printing *	Mono printing	Maximum ISO A-series paper size *	A4
Duplex printing *	✓	Maximum print size	216 x 356 mm
Maximum resolution *	1200 x 1200 DPI	Paper tray media types *	Banner, Labels, Letterhead, Plain paper, Pre-printed, Thicker paper, Thin paper
Print speed (black, normal quality, A4/US Letter) *	55 ppm	ISO A-series sizes (A0...A9) *	A4, A5, A6
Duplex print speed (black, normal quality, A4/US Letter)	39.5 ppm	ISO B-series sizes (B0...B9)	B5, B6
Warm-up time	25 s	Non-ISO print media sizes	Folio, Legal, Letter
Time to first page (black, normal)	4.5 s	Custom media width	70 - 216 mm
N-in-1 print function	✓	Custom media length	140 - 356 mm
N-up printing	2, 4, 6, 8, 9, 16, 25	Paper tray media weight	60 - 120 g/m ²
Watermark printing	✓	Multi-Purpose Tray media weight	60 - 220 g/m ²
Economical printing	✓	Ports & interfaces	
Secure printing	✓	Direct printing *	✓
Cover page printing function	✓	USB port	✓
Booklet printing function	✗	USB 2.0 ports quantity	1
Poster printing function	✓	Optional connectivity	Ethernet, Wireless LAN
Borderless printing	✗	Network	
DVD/CD printing	✗	Wi-Fi *	✗
Copying		Ethernet LAN *	✓
Duplex copying *	✓	Cabling technology	10/100/1000Base-T(X)
Duplex copying mode	Auto	Ethernet LAN data rates	10,100,1000 Mbit/s
Copying *	Mono copying	Security algorithms	HTTPS, IPSec, SNMPv3, TLS

Copying		Network	
Maximum copy resolution *	600 x 600 DPI	Mobile printing technologies	Apple AirPrint, Mopria Print Service
Maximum copy size	A4	Performance	
Copy speed (black, normal quality, A4)	55 cpm	Maximum internal memory	3500 MB
Time to first copy (black, normal)	6 s	Memory slots	1
Maximum number of copies	999 copies	Card reader integrated	✗
Copier resize	25 - 400%	Internal memory *	1500 MB
N-in-1 copy function	✓	Compatible memory cards	SD
N-in-1 copy function (N=)	2, 4	Built-in processor	✓
Copy programming function	✓	Processor family	ARM Cortex
Book copy function	✗	Processor model	A53
ID-card copy function	✓	Processor frequency	1400 MHz
Scanning		Processor cores	2
Duplex scanning *	✓	Introduction year	2023
Duplex scanning mode	Auto	Sound pressure level (printing)	56 dB
Scanning *	Colour scanning	Sound pressure level (copying)	56 dB
Optical scanning resolution *	600 x 600 DPI	Sound pressure level (standby)	30 dB
Optical scanning resolution (black)	600 x 600 ppi	Design	
Optical scanning resolution (colour)	300 x 300 ppi	Product colour *	Black, White
Optical scanning resolution (ADF)	600 x 600 DPI	Market positioning *	Business
Maximum scan resolution	600 x 600 DPI	Built-in display *	✓
Maximum scan area	210 x 297 mm	Display	LCD
Scanner type *	Flatbed & ADF scanner	Display diagonal	17.8 cm (7")
Scan technology	CIS/CCD	Control type	Touch
Scan to	E-mail, FTP, File, Image, PC, Print, SMB, TWAIN, USB, WIA	Colour display	✓
Scan speed (colour)	40 ppm	Power	
Scan speed (black)	60 ppm	Power consumption (max)	1287 W
Duplex scan speed (colour)	80 ppm	Power consumption (printing)	704.1 W
Duplex scan speed (black)	120 ppm	Power consumption (copying)	719 W
Image formats supported	JPEG, MMR, TIFF	Power consumption (ready)	59.8 W
Document formats supported	PDF, XPS	Power consumption (sleep)	0.6 W
Greyscale levels	256	Power consumption (off)	0.1 W
Scan drivers	TWAIN, WIA	Energy Star Typical Electricity Consumption (TEC)	0.78 kWh/week
Fax		AC input voltage	220 - 240 V
Duplex faxing	✓	AC input frequency	50/60 Hz
Faxing *	Mono faxing	System requirements	
Fax resolution (black)	400 x 400 DPI	Windows operating systems supported	✓
Fax transmission speed	3 sec/page		Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Modem speed	33.6 Kbit/s	Mac operating systems supported	
Fax memory	256 pages	Linux operating systems supported	✓
Auto-redialing	✓	Other operating systems supported	ChromeOS
Speed dialling	✓	Operational conditions	
Fax forwarding	✓	Operating relative humidity (H-H)	15 - 80%
Fax delayed sending	✓	Storage temperature (T-T)	-20 - 40 °C
Features		Operating temperature (T-T)	10 - 32.5 °C
Recommended duty cycle	0 - 27500 pages per month	Storage relative humidity (H-H)	10 - 90%
Maximum duty cycle *	250000 pages per month	Operating altitude	0 - 3500 m
Duplex functions *	Copy, Fax, Print, Scan	Sustainability	
Digital sender	✓	Sustainability compliance	✓
Ink tank system	✗	Sustainability certificates	EPEAT Gold
Number of print cartridges *	1	Weight & dimensions	
Printing colours *	Black		
Page description languages	IBM ProPrinter, JPEG, PCL 6, PCLm, PDF, PWG, PostScript 3, TIFF, URF, XPS		
Printer fonts	Bitmap		
All-In-One-multitasking	✓		

Features		Weight & dimensions	
Country of origin	Vietnam	Width	480 mm
Replacement cartridges	TK-3430 (25.000 pagina's)	Depth	495 mm
Input & output capacity		Height	590 mm
Total number of input trays *	2	Weight	24.7 kg
Total input capacity *	600 sheets	Packaging data	
Total output capacity *	500 sheets	Package width	633 mm
Paper tray 1 input capacity	500 sheets	Package depth	570 mm
Multi-Purpose tray	✓	Package height	710 mm
Multi-Purpose tray input capacity	100 sheets	Package weight	32 kg
Auto document feeder (ADF)	✓	Packaging content	
Auto document feeder (ADF) input capacity	100 sheets	Cartridge(s) included	✓
Maximum number of input trays	6	Included cartridge capacity (black)	10000 pages
Maximum input capacity	2600 sheets	Imaging unit included	✓
		Cables included	AC
		Technical details	
		Compliance certificates	CE, GS mark, REACH, RoHS, cTUVus



0632983080078



632983080078

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.