

## DELL P Series P2425H tietokoneen litteä näyttö 61 cm (24") 1920 x 1080 pikseliä Full HD LCD musta

Tuotemerkki : DELL Tuoteperhe: P Series Tuotekoodi: DELL-P2425H

Tuotteen nimi: P2425H

DELL P Series P2425H. Näytön halkaisija: 61 cm (24"), Näytön erottelutarkkuus: 1920 x 1080 pikseliä, HD-tyyppi: Full HD, Näytön teknologia: LCD, Vasteaika (tyypillinen): 8 ms, Vakiokuvasuhde: 16:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäänrakennettu USB-keskus, USB-keskuksen versio: 3.2 Gen 1 (3.1 Gen 1). VESA-kiinnitys, Korkeudensäätö. Tuotteen väri: musta





| Display   |   | Ergonomics  |  |
|---|---|---|--|
| Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type * LED backlight Backlight type Touchscreen * Display brightness (typical)                                       | 61 cm (24") 1920 x 1080 pixels Full HD 16:9 LCD IPS  ✓ LED  X 250 cd/m²   | Pivot Pivot angle Swivelling Swivel angle range Tilt adjustment Tilt angle range On Screen Display (OSD) Plug and Play LED indicators   | ✓ -90 - 90° ✓ -45 - 45° ✓ -5 - 21° × ✓   |
| Response time *   | 8 ms  | Power   |  |
| Anti-glare screen Screen shape *  Supported graphics resolutions  Supported video modes Contrast ratio (typical) * Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * | Flat 640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1600 x 900, 1920 x 1080 (HD 1080) 480p, 576p, 720p, 1080p 1500:1 100 Hz 178° 178° 16.7 million colours | Energy efficiency class (SDR) * Energy efficiency class (HDR) * Energy consumption (SDR) per 1000 hours * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (off) AC input voltage AC input frequency Input current Power supply type | C Not available  12 kWh  11.7 W 0.3 W 65 W 0.3 W 100 - 240 V 50/60 Hz 1.5 A Internal |
| Response time (fast) Pixel pitch Pixel density Horizontal scan range  | 5 ms<br>0.2745 x 0.2745 mm<br>92.53 ppi<br>30 - 110 kHz   | Energy efficiency scale European Product Registry for Energy Labelling (EPREL) code  Operational conditions   | A to G<br>1865623  |
| Vertical scan range<br>Viewable size, horizontal  | 48 - 100 Hz<br>52.7 cm  | Operating temperature (T-T)<br>Storage temperature (T-T)  | 0 - 40 °C<br>-20 - 60 °C   |

| Display   |                                 | Operational conditions   |   |
|---|---------------------------------|--|---|
| Viewable size, vertical<br>Viewable size diagonal<br>Surface hardness<br>sRGB coverage (typical)  | 29.6 cm<br>60.5 cm<br>3H<br>99% | Operating relative humidity (H-H)<br>Storage relative humidity (H-H)<br>Operating altitude<br>Non-operating altitude   | 10 - 80%<br>5 - 90%<br>0 - 5000 m<br>0 - 12192 m                                  |
| Dell ComfortView technology   | <b>✓</b>                        | Weight & dimensions  |   |
| Performance NVIDIA G-SYNC *   |                                 | Width (with stand) Depth (with stand)  | 538.6 mm<br>181.8 mm  |
| AMD FreeSync * Flicker-free technology Low Blue Light technology Windows operating systems supported Mac operating systems supported Multimedia | X X Windows 10, Yes MacOS       | Height (with stand) Weight (with stand) Width (without stand) Depth (without stand) Height (without stand) Weight (without stand) Bezel width (side) Bezel width (top) | 364 mm<br>4.61 kg<br>538.6 mm<br>50 mm<br>314.2 mm<br>3.12 kg<br>5.8 mm<br>5.8 mm |
| Built-in speaker(s) *   | x                               | Bezel width (bottom)   | 1.2 cm  |
| Built-in camera *   | ×                               | Packaging data   | 1.2 cm  |
| Design Product colour *   | Black                           | Package weight USB cable length  | 6.78 kg<br>1.8 m  |
| Front bezel colour  | Black                           | Packaging content  |   |
| Feet colour   | Grey                            | Stand included   | /   |
| Ports & interfaces  |                                 | Cables included  | AC, DisplayPort, USB Type-A   |
| Built-in USB hub *  | ✓                               | Quick start guide  | ✓   |
| USB hub version   | 3.2 Gen 1 (3.1 Gen 1)           | DisplayPort cable length   | 1.8 m   |
| Number of USB Type-B upstream ports quantity  | 1                               | HDMI cable length  Sustainability  | 1.8 m   |
| USB Type-A downstream ports   | 3                               | •  |   |
| quantity USB Type-C downstream ports quantity   | 1                               | Sustainability compliance Sustainability certificates Doesn't contain  | TÜV mark Arsenic, Mercury, PVC/BFR  |
| USB Power Delivery (USB PD)   | ✓                               | Carbon footprint   |   |
| USB Power Delivery up to<br>VGA (D-Sub) ports quantity<br>HDMI *  | 15 W<br>1                       | Total carbon footprint (kg of CO2e)<br>Carbon emissions, manufacturing<br>(kg of CO2e)   | 138<br>67   |
| HDMI ports quantity HDMI version  | 1<br>1.4                        | Carbon emissions, logistics (kg of CO2e)   | 10  |
| DisplayPorts quantity DisplayPort version   | 1<br>1.2                        | Carbon emissions, energy usage (kg of CO2e)  | 58  |
| Headphone out *   | ×                               | Carbon emissions, end-of-life (kg of CO2e)   | 3   |
| HDCP  | 1.4                             | Total carbon emissions, w/o use  | 80  |
| HDCP version  | 1.4                             | phase (kg of CO2e) PAIA version  | GaBi version 1, 2024  |
| AC (power) in   | <b>/</b>                        | Brand-specific features  | Gdb1 VC131011 1, 2024   |
| Ergonomics  |                                 | •  |   |
| VESA mounting * Panel mounting interface Cable management   | 100 x 100 mm                    | Dell Display Manager (DDM)<br>compatibility  | •   |
| Cable lock slot *   | Vancianton                      |  |   |
| Cable lock slot type  | Kensington                      |  |   |
| Height adjustment * Adjustable height (max)   | <b>✓</b><br>15 cm               |  |   |





5397184821701

0884116468684



884116468684

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.