

DELL P Series P2725HE tietokoneen litteä näyttö 68,6 cm (27") 1920 x 1080 pikseliä Full HD LCD musta

Tuotemerkki : DELL Tuoteperhe: P Series Tuotekoodi: DELL-P2725HE

Tuotteen nimi: P2725HE

DELL P Series P2725HE. Näytön halkaisija: 68,6 cm (27"), Näytön erottelutarkkuus: 1920 x 1080 pikseliä, HD-tyyppi: Full HD, Näytön teknologia: LCD, Vasteaika (tyypillinen): 8 ms, Vakiokuvasuhde: 16:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäänrakennettu USB-keskus, USB-keskuksen versio: 3.2 Gen 1 (3.1 Gen 1). VESA-kiinnitys, Korkeudensäätö. Tuotteen väri: musta





Display		Ergonomics	
Display Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type * LED backlight Backlight type Touchscreen * Display brightness (typical) Response time * Anti-glare screen Screen shape *	68.6 cm (27") 1920 x 1080 pixels Full HD 16:9 LCD IPS LED X 300 cd/m² 8 ms Flat	Cable management Cable lock slot * Cable lock slot type Height adjustment * Height adjustment Pivot Pivot angle Swivelling Swivel angle range Tilt adjustment Tilt angle range On Screen Display (OSD)	Kensington 15 cm -90 - 90° -45 - 45° -5 - 21°
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1600	Plug and Play LED indicators Power	<i>* *</i>
Supported video modes Contrast ratio (typical) * Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast) Pixel pitch	x 900, 1920 x 1080 (HD 1080) 480p, 576p, 720p, 1080p 1500:1 100 Hz 178° 16.7 million colours 5 ms 0.3114 x 0.3114 mm	Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (off) AC input voltage AC input frequency Input current European Product Registry for Energy Labelling (EPREL) code	16.2 W 0.4 W 180 W 0.3 W 100 - 240 V 50/60 Hz 2 A
Pixel density Horizontal scan range Vertical scan range Viewable size, horizontal	81.57 ppi 30 - 110 kHz 48 - 100 Hz 59.8 cm	Operational conditions Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -20 - 60 °C

Display		Operational conditions	
Viewable size, vertical Viewable size diagonal Surface hardness sRGB coverage (typical)	33.6 cm 68.6 cm 3H 99%	Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	10 - 80% 5 - 90% 0 - 5000 m 0 - 12192 m
Dell ComfortView technology	✓	Weight & dimensions	
Performance NVIDIA G-SYNC * AMD FreeSync * Flicker-free technology Low Blue Light technology Windows operating systems supported Mac operating systems supported Multimedia	X X Windows 10, Yes MacOS	Width (with stand) Depth (with stand) Height (with stand) Weight (with stand) Width (without stand) Depth (without stand) Height (without stand) Weight (without stand) Bezel width (side) Bezel width (top)	610.7 mm 192.3 mm 384.6 mm 6.01 kg 610.7 mm 50 mm 354.7 mm 4.36 kg 6.4 mm 6.4 mm
Built-in speaker(s) *	×	Bezel width (bottom)	1.2 cm
Built-in camera *	X	Packaging data	
Design		Package weight	8.67 kg
Product colour * Front bezel colour Feet colour	Black Black Grey	Packaging content Stand included	✓
Ports & interfaces		Sustainability	_
Built-in USB hub * USB hub version Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity	3.2 Gen 1 (3.1 Gen 1) 1	Sustainability compliance Sustainability certificates Doesn't contain Carbon footprint Total carbon footprint (kg of CO2e)	ENERGY STAR, TCO Arsenic, Mercury, PVC/BFR
USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD)	1	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg of CO2e)	1021680
USB Power Delivery up to HDMI * HDMI ports quantity HDMI version	90 W ✓ 1 1.4	Carbon emissions, end-of-life (kg of CO2e) Total carbon emissions, w/o use phase (kg of CO2e) PAIA version	9 127 GaBi version 1, 2024
DisplayPorts quantity DisplayPort version Headphone out * HDCP HDCP version	2 1.4 X 1.4	Other features RJ-45 ports quantity Compliance certificates Brand-specific features Dell Display Manager (DDM)	1 RoHS, TÜV mark
AC (power) in	/	compatibility	✓
Ergonomics			
VESA mounting *	/		

100 x 100 mm

Panel mounting interface





5397184821763

0884116468769



884116468769

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.