## **PHILIPS**

## Philips 27M1N3200ZS/00 computer monitor 68.6 cm (27") 1920 x 1080 pixels Full HD LED Black

Product name: 27M1N3200ZS/00

Gaming Monitor 27M1N3200ZS Full HD gaming monitor

Philips 27M1N3200ZS/00 computer monitor 68.6 cm (27") 1920 x 1080 pixels Full HD LED Black:

This gaming monitor is an all-around display for intense PC games. FreeSync, a rapid 165 Hz refresh rate and 1 ms response time deliver smooth gameplay. The virtually frameless display with Ultra Wide-Color enhances the immersive visual experience.

Philips 27M1N3200ZS/00. Display diagonal: 68.6 cm (27"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LED, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. VESA mounting. Product colour: Black





Display		Ergonomics	
Display diagonal *	68.6 cm (27")	Tilt adjustment	1
Display resolution *	1920 x 1080 pixels	Tilt angle range	-5 - 20°
HD type *  Native aspect ratio *  Display technology *  Panel type *  Backlight type	Full HD 16:9 LED IPS W-LED	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Display brightness (typical)	250 cd/m²	Number of OSD languages	21
Response time *	4 ms	Plug and Play	✓
Anti-glare screen	✓	LED indicators	Operation, Stand-by
Screen shape *	Flat	Power	
Supported graphics resolutions	1920 x 1080 (HD 1080)	Energy efficiency class (SDR) *	E
Supported video modes	1080p 16:9	Energy consumption (SDR) per 1000	21 kWh
Aspect ratio  Contrast ratio (typical) *	1100:1	hours *	
Dynamic contrast ratio marketing		Power consumption (typical) *	28.2 W
name	Mega Infinity DCR	Power consumption (standby) * Power consumption (off)	0.5 W 0.3 W
Maximum refresh rate *	165 Hz	AC input voltage	100 - 240 V
Viewing angle, horizontal	178°	AC input frequency	50 - 60 Hz
Viewing angle, vertical	178°	Power supply type	Internal
Display number of colours *	16.7 million colours	Energy efficiency scale	A to G
Response time (fast) Pixel pitch	1 ms 0.3114 x 0.3114 mm	European Product Registry for Energy Labelling (EPREL) code	1527514
Pixel density	81.59 ppi	Operational conditions	
Vertical scan range	48 - 165 Hz	•	0 - 40 °C
Viewable size, horizontal	59.8 cm	Operating temperature (T-T) Storage temperature (T-T)	-20 - 60 °C
Viewable size, vertical	33.6 cm	Operating relative humidity (H-H)	20 - 80%
Display diagonal (metric)	68.5 cm	Operating altitude	0 - 3658 m
DDC/CI	✓	Non-operating altitude	0 - 12192 m
Haze rate	25%	, 3	
Surface hardness	3H	Weight & dimensions	610
sRGB coverage (typical)	122%	Width (with stand)	612 mm

Display		Weight & dimensions	
NTSC coverage (typical) Adobe RGB coverage Display sRGB	107% 90.4% ✓	Depth (with stand) Height (with stand) Weight (with stand)	193 mm 449 mm 5.15 kg
Performance		Width (without stand)	612 mm
AMD FreeSync *  AMD FreeSync type	type FreeSync Premium Weight (without stand)	Height (without stand)	55 mm 365 mm 3.7 kg
Component video sync Flicker-free technology	Separate sync  ✓	Packaging data	
Design	Gaming	Package width Package depth Package height	780 mm 186 mm 525 mm
Product colour *	Black	Package weight	9.28 kg
Detachable stand	✓	Packaging content	
Ports & interfaces		Stand included	✓
HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Audio output	<b>✓</b> 2	Cables included Manual	DisplayPort, HDMI, Power ✓
	2.0	Sustainability	
	1 1.2 ✓	Sustainability compliance Doesn't contain	✓ Mercury, PVC/BFR
HDCP	✓	Other features	
HDCP version	1.4/2.2	Low input lag	✓
Ergonomics		Exterior finish type	Textured
VESA mounting *  ✓ Panel mounting interface 100 x 10	✓ 100 x 100 mm	Picture enhancement Recyclable packaging material	SmartImage game 100%  CPL CF Marks FCC Class Builder 2003
Wall mountable  Cable lock slot *	<i>*</i>	Regulatory Approvals	CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU ROHS; TUV/ISO9241-307; TUV-BAUART
Cable lock slot type	Kensington	EasyRead mode	<b>✓</b>
	-	LowBlue mode	✓
		Compliance certificates	CB, Federal Communications Commission (FCC), ICES, RoHS, cTUVus
		Mean time between failures (MTBF)	50000 h



8712581802738

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.