ATEN

ATEN SN3401P päätepalvelin RS-232/422/485

Tuotemerkki: ATEN Tuotekoodi: SN3401P-AX

Tuotteen nimi: SN3401P

ATEN SN3401P. Virtalähteen malli: DC, PoE, Tehonkulutus (maks.): 1,3 W, Virrankulutus: 1,18 W. LED-merkkivalot: Teho, Tila. Tuotteen leveys: 117 mm, Tuotteen syvyys: 98 mm, Tuotteen korkeus: 26 mm. Tuotteen väri: musta, Kotelon materiaali: Metalli, Turvallisuus: UL 60950-1, UL 62368-1. Jalkatyynyjen lukumäärä: 4 kpl





Technical details		Weight & dimensions	
Serial ports quantity * Serial interface type Isolation Surge protection voltage Ethernet LAN data rates	1 RS-232/422/485 1.5 kV 2 kV 10,100 Mbit/s	Weight Package width Package depth Package height Package weight	210 g 59 mm 239 mm 160 mm 420 g
Electrostatic Discharge (ESD) protection	8 kV	Operational conditions	
Data transfer rate Networking standards Flow control support	100 Mbit/s IEEE 802.3af ✓	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 60 °C -40 - 75 °C 5 - 95%
Baud rate	921.6 Kbit/s	Design	
RS-232 signals RS-422 signals RS-485 signals Data bits	CTS, DCD, DSR, DTR, GND, RTS, RXD, TXD GND, RxD+, RxD-, TxD+, TxD- Data+, Data-, GND, RxD+, RxD-, TxD+, TxD- 5, 6, 7, 8 DTR/DSR, RTS/CTS, XON/XOFF Even, Mark, No, Odd, Space 1, 1.5, 2 RoHS	Product colour Housing material Reset button DIN rail mounting Safety	Black Metal UL 60950-1, UL 62368-1
Flow Control type		Packaging content	
Parity bit Stop bits Compliance certificates Ports & interfaces		DIN rail kit included Terminal block included Number of foot pads User guide	4 pc(s)
Ethernet LAN	✓	Logistics data	
Ethernet LAN (RJ-45) ports Terminal block port	1	Country of origin Products per master (outer) case	Taiwan 10 pc(s)
Power		Master (outer) case gross weight	5.51 kg
Power source type Power consumption (max) Power consumption (typical) Input voltage Input frequency Output voltage	DC, PoE 1.3 W 1.18 W 100 - 240 V 50 - 60 Hz 9 - 48 V	Package volume Master (outer) case volume Master (outer) case length Master (outer) case width Master (outer) case height Master (outer) case net weight	2265.35 cm ³ 27467.33 cm ³ 490 mm 315 mm 178 mm 3.3 kg
Indication		Sustainability	
LED indicators	Power, Status	Sustainability compliance	✓
Weight & dimensions		Sustainability certificates	UL ECOLOGO
Width Depth	117 mm 98 mm		

		_	••	
Wei	aht	δı	dime	nsions

Height 26 mm



4710469341564

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.