Verbatim CMH-14 USB Type-C 5000 Mbit/s Silver

Brand : Verbatim

Product name : CMH-14

Product code: 32154

- Transform a single USB-C® port into fourteen ports including dual HDMI, VGA, and gigabit ethernet connection
- 2 x HDMI, 1 x VGA, 1 x RJ45, 3 x USB-A 3.2 Gen1, 1 x USB-C 3.2 Gen1, 2 x USB-A 2.0, 1 x SD card slot, 1 x microSD card slot, 1 x Audio jack, 1 x USB-C PD
- Triple 1080p video output
- Dual 4K HDMI display support
- VGA socket for legacy monitor support
- Equipped with a combination of USB-A and USB-C ports for connecting multiple devices
- Integrated SD and microSD memory card slots
- Gigabit ethernet port for high speed, wired internet acess
- Dual USB-C Power Delivery - charge devices while using the hub wth pass-through charging
2 x HDMI, 4K60Hz, 4K30Hz, 1 x VGA, 1080p, 1 x RJ45, 1Gb/s, 3 x USB-A 3.2 Gen1, 5Gb/s, 1 x USB-C 3.2 Gen1, 5Gb/s, 2 x USB-A 2.0, 1 x Audio jack, 1 x SD 3.0, 1 x microSD 3.0, 1 x USB-C PD, 40mm x 55.4mm x 15mm

Ports & interfaces

Host interface *	USB Type-C
Hub interfaces *	HDMI, RJ-45, USB 2.0, USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 1 (3.1 Gen 1) Type-C, USB Type-C, VGA
USB 2.0 ports quantity	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	1
HDMI ports quantity	2
VGA (D-Sub) ports quantity	1
Combo headphone/mic port	✔
Ports quantity *	14
Ethernet LAN (RJ-45) ports	1
Card reader slot	2
Compatible memory cards	MicroSD (TransFlash), SD

Features

Data transfer rate *	5000 Mbit/s
Maximum refresh rate	60 Hz
Product colour	Silver
Housing material	Acrylonitrile butadiene styrene (ABS), Aluminium
USB Power Delivery (USB PD)	✔
USB Power Delivery up to	100 W
HD type	4K Ultra HD

Weight & dimensions

Width	55.4 mm
Depth	140 mm
Height	15 mm
Weight	125 g

Packaging data

Quantity per pack	1 pc(s)
Package width	100 mm
Package depth	200 mm
Package height	22 mm
Package weight	186 g
Package type	Hanging box

Packaging content

Quick start guide	✔

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	10 - 85%

Logistics data

Packs per box (outer)	40
Box (outer) per layer	8
Products per pallet	960 pc(s)
Master (outer) case width	245 mm
Layers per pallet	3 pc(s)
Master (outer) case length	435 mm
Master (outer) case height	290 mm

Features

LED indicators	✗
Cable length	0.15 m
Country of origin	China
Certification	EAC/CE/UKCA/FCC RoHS/REACH

Network

Ethernet interface type	Gigabit Ethernet

Power

Output voltage	5 V
Output current	0.9 A

System requirements

Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8
Mac operating systems supported	Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.7.5 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Other operating systems supported	ChromeOS

Logistics data

Master (outer) case gross weight	8.6 kg
Products per master (outer) case	40 pc(s)
Shipping (inner) case width	11.2 cm
Shipping (inner) case length	41.5 cm
Shipping (inner) case height	13 cm
Shipping (inner) case gross weight	2.01 kg
Products per shipping (inner) case	10 pc(s)

Technical details

Master (outer) cases per pallet	24 pc(s)

0023942321545

023942321545

(01)50023942321540

(01)20023942321549