

D-Link DGS-3130-54PS/E verkkokytkin Hallittu L3 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki Harmaa



Tuotemerkki : D-Link

Tuotekoodi: DGS-3130-54PS/E

Tuotteen nimi : DGS-3130-54PS/E

D-Link DGS-3130-54PS/E. Kytkin tyyppi: Hallittu, Kytinkerros: L3. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 48, USB 2.0 - porttien määrä: 1, Console-portti: RJ-45. MAC-osoitetaulukko: 16384 entries, Kytkentäkapasiteetti: 216 Gbit/s. Verkkostandardit: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1v, IEEE 802.1w, IEEE 802.1x, IEEE.... Virtaliitin: AC-in-liitin. Power over Ethernet -tuki. Telineasennus

Management features		Security	
Switch type *	Managed	Loop protection	✓
Switch layer	L3	BPDU filtering/protection	✓
Quality of Service (QoS) support	✓	Authentication	MAC-based authentication, Port-based authentication, Web-based authentication
Web-based management	✓	Password protection	✓
ARP inspection	✓	Queue scheduling algorithms	Deficit weighted round robin (DWRR), SP, WRR+SP, Weighted Round Robin (WRR)
System event log	✓		
	RFC 1213; RFC 4188; RFC 1157, 2571-2576; RFC 1907; RFC 1757, 2819; RFC 2021; RFC 1398, 1643, 1650, 2358, 2665; RFC 2674 802.1p	Multicast features	
MIB support	2233, 2863 IF MIB; RFC 2618; RFC 2620; RFC 2925; RFC 2674, 4363; RFC 1065, 1066, 1155, 1156, 2578; RFC 1215; RFC 1212; RFC 1215; RFC 1157, 2571-2576; RFC 4022; RFC 4113; RFC 4293; RFC 2737	Multicast support	✓
		Multicast features	Controllable multicast
Ports & interfaces		Protocols	
Basic switching RJ-45 Ethernet ports quantity *	48	GARP VLAN Registration Protocol (GVRP)	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Routing protocols	RIP
SFP+ module slots quantity	4	Design	
Fiber optic connector	SFP+	Rack mounting *	✓
Console port	RJ-45	Stackable *	✓
USB 2.0 ports quantity	1	Product colour	Grey
Power connector	AC-in jack	LED indicators	✓
Network		Number of fans	4 fan(s)
		Performance	
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1v, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3ah, IEEE 802.3at, IEEE 802.3az, IEEE 802.3x	Physical stacking (units)	9
10G support *	✓	Virtual stacking (units)	32
Copper ethernet cabling technology	10BASE-T, 10GBASE-T, 100BASE-TX, 1000BASE-T	Noise level	56 dB
Port mirroring	✓	Mean time between failures (MTBF)	356876 h
Flow control support	✓	Power	
Link aggregation	✓	Power source *	DC/PoE
Broadcast storm control	✓	Redundant power supply (RPS) support	✓
Spanning tree protocol	✓	AC input voltage	100 - 240 V
Head-of-line (HOL) blocking	✓	AC input frequency	50 - 60 Hz
VLAN support	✓	Power consumption (max)	474.51 W
		Power over Ethernet (PoE)	
		Power over Ethernet (PoE) *	✓
		Power over Ethernet plus (PoE+) ports quantity	48
		Total Power over Ethernet (PoE) budget	370 W

Network		Operational conditions	
Virtual LAN features	MAC address-based VLAN, Port-based VLAN, Private VLAN, Tagged VLAN, Voice VLAN	Operating temperature (T-T)	0 - 50 °C
Number of VLANs	4000	Storage temperature (T-T)	-40 - 70 °C
Data transmission		Operating relative humidity (H-H)	10 - 90%
Switching capacity *	216 Gbit/s	Storage relative humidity (H-H)	5 - 90%
Forwarding rate	161 Mpps	Heat dissipation	1619.03 BTU/h
MAC address table *	16384 entries	Weight & dimensions	
Number of queues	8	Width	440 mm
Jumbo frames support	✓	Depth	430 mm
Packet buffer memory	2 MB	Height	44 mm
Security		Weight	6.2 kg
DHCP features	DHCP client, DHCP relay, DHCP server, DHCP snooping		
Access Control List (ACL)	✓		
Access Control List (ACL) egress	512		
Access Control List (ACL) ingress	2048		
IGMP snooping	✓		
Security algorithms	SNMP, SNMPv3, SSH-2, SSL/TLS		
SSH/SSL support	✓		



0790069469992



790069469992

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.