



LG 37BH7N-H infonäyttö Digitaalinen litteä infotaulu 94 cm (37") Wi-Fi 700 cd/m² Full HD musta WebOS 24/7

Tuotemerkki : LG

Tuotekoodi: 37BH7N-H



Tuotteen nimi : 37BH7N-H

LG 37BH7N-H. Tuotteen muotoilu: Digitaalinen litteä infotaulu. Näytön halkaisija: 94 cm (37"), Näytön erottelutarkkuus: 1920 x 540 pikseliä, Näytön kirkkaus: 700 cd/m², HD-tyyppi: Full HD. Wi-Fi. Toiminta-aika (tunteja/päiviä): 24/7. Käyttöjärjestelmä asennettu: WebOS. Tuotteen väri: musta



Display		Design	
Panel type	IPS	Product design *	Digital signage flat panel
LED backlight	✓	Placement supported *	Indoor
LED backlighting type	Edge-LED	Orientation	Horizontal/Vertical
Display diagonal *	94 cm (37")	Product colour *	Black
Display resolution *	1920 x 540 pixels	VESA mounting *	✓
Display brightness *	700 cd/m ²	Panel mounting interface	400 x 200 mm
HD type *	Full HD	Bezel width (bottom)	1.56 cm
Touchscreen *	✗	Bezel width (side)	9.3 mm
Native aspect ratio	32:9	Bezel width (top)	1.56 cm
Response time	14 ms	Performance	
Contrast ratio (typical)	1000:1	Operating hours (hours/days)	24/7
Contrast ratio (dynamic)	1000000:1	Power	
Viewing angle, horizontal	178°	Power consumption (typical) *	40 W
Viewing angle, vertical	178°	Power consumption (off)	1 W
Display number of colours	16.7 million colours	Power consumption (max)	50 W
Panel life	50000 h	AC input voltage	120 V
Native refresh rate	60 Hz	AC input frequency	50/60 Hz
Haze rate	25%	Computer system	
Colour gamut	72%	Internal memory	16 GB
Ports & interfaces		Operating system installed	WebOS
HDMI ports quantity *	3	Operating system version	6.0
HDMI input ports quantity	2	Weight & dimensions	
HDMI output ports quantity	1	Display width	922.3 mm
DisplayPorts quantity *	1	Display depth	43.5 mm
USB port *	✓	Display height	288.3 mm
USB ports quantity	1	Display weight	7 kg
USB version	2.0	Packaging data	
USB connector type	USB Type-A	Package weight	9 kg
Ethernet LAN *	✓	Packaging content	
Ethernet LAN (RJ-45) ports	1	Remote control included	✓
Wi-Fi *	✓	Cables included	AC, Phone
RS-232C	✓		
Remote (IR) input	1		

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 80%



0195174069998



195174069998

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.