

j5create JCD381-N USB Type-C™ Dual HDMI Mini Dock-Ethernet/ USB 3.1 HUB / PD2.0

Brand : j5create

Product code: JCD381-N

Product name : JCD381-N USB Type-C™ Dual HDMI Mini Dock-Ethernet/ USB 3.1 HUB / PD2.0



JCD381 USB Type-C Dual HDMI Mini Dock-Ethernet/ USB 3.1 Hub / PD2.0, includes 2x HDMI ports and 3x USB ports, Metallic Champagne

[j5create JCD381-N USB Type-C™ Dual HDMI Mini Dock-Ethernet/ USB 3.1 HUB / PD2.0:](#)

The USB-C® Dual HDMI™ Mini Dock provides extra connectivity for your USB-C® computer, featuring data transfer, power delivery and video displays. Easily add two additional USB™ computer peripherals, two HDMI™ monitors, and a Gigabit Ethernet connection through your USB-C® port. When connected to a power source, the USB-C® input charging port allows you to continue charging your laptop or smartphone. Its compact and lightweight design, making it great for use on the go.



Ports & interfaces		Software	
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C		Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura, Mac OS X 14.0 Sonoma, MacOS
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	3		
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1	Mac operating systems supported	
USB Power Delivery (USB PD)	✓		
USB Power Delivery up to	60 W		
HDMI ports quantity *	2		
USB Type-C DisplayPort Alternate Mode	✗		
Network		Operational conditions	
Ethernet LAN (RJ-45) ports	1	Operating temperature (T-T)	0 - 40 °C
Ethernet LAN data rates	10,100,1000 Mbit/s	Storage temperature (T-T)	-10 - 65 °C
		Operating relative humidity (H-H)	0 - 85%
		Storage relative humidity (H-H)	0 - 85%
Performance		Weight & dimensions	
HD type	4K Ultra HD	Width	130 mm
Number of displays supported	2	Depth	15 mm
Maximum refresh rate	30 Hz	Height	54 mm
Product colour *	Beige, White	Weight	115.5 g
Hub interfaces	HDMI, PS/2, USB 3.2 Gen 1 (3.1 Gen 1) Type-A	Packaging data	
Plug and Play	✗	Quantity per pack	1 pc(s)
Housing material	Aluminium	Package width	193 mm
Country of origin	Taiwan	Package depth	125 mm
		Package height	22.5 mm
		Package weight	194.5 g
Power		Packaging content	
Input current	3 A	Quick start guide	✓
Power supply	2.25 W	Manual	✓
Output voltage	20 V		
Output current	0.45 A		

Software		Packaging content	
Windows operating systems supported	Windows 10, Windows 11, Yes	Packaging content	1 x JCD381 USB-C® Dual HDMI™ Mini Dock, 1 x Quick Installation Guide
Technical details			
Warranty period		2 year(s)	
Other features			
Cable length		0.2 m	
Maximum operating temperature		40 °C	



4712795081831

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 02-FEB-2025. Prints or copies of Information are only valid on the printed Publication date