



# Lenovo ThinkSystem SR665 V3 server Rack (2U) AMD EPYC 9354 3.25 GHz 32 GB DDR5-SDRAM 1800 W



**Brand :** Lenovo      **Product family:** ThinkSystem      **Product code:** 7D9AA01YEA  
**Product name :** SR665 V3

- No OS
- AMD EPYC 9354 (256MB Cache, 3.25GHz)
- 32GB (4800MHz) DDR5-SDRAM (1 x 32)
- AMD EPYC 9354 (256MB Cache, 3.25GHz), 32GB DDR5-SDRAM (4800MHz), LAN, 1800W, No OS

## Lenovo ThinkSystem SR665 V3 server Rack (2U) AMD EPYC 9354 3.25 GHz 32 GB DDR5-SDRAM 1800 W:

The Lenovo ThinkSystem SR665 V3 is a 2-socket 2U server that features the AMD EPYC 9004 "Genoa" family of processors. With up to 128 cores per processor and support for the new PCIe 5.0 standard for I/O, the SR665 V3 offers the ultimate in two-socket server performance in a 2U form factor.

This product guide provides essential pre-sales information to understand the ThinkSystem SR665 V3 server, its key features and specifications, components and options, and configuration guidelines. This guide is intended for technical specialists, sales specialists, sales engineers, IT architects, and other IT professionals who want to learn more about the SR665 V3 and consider its use in IT solutions.

Processor		Design	
Processor manufacturer *	AMD	Product colour	Black
Processor family *	AMD EPYC	Rack mounting	✓
Processor model *	9354	<b>Performance</b>	
Processor frequency *	3.25 GHz	Performance management	XClarity Controller Platinum
Processor cores	32	Trusted Platform Module (TPM)	✓
Processor cache	256 MB	Trusted Platform Module (TPM) version	2.0
Number of processors installed	1	<b>Software</b>	
<b>Memory</b>		Operating system installed *	✗
Internal memory *	32 GB	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi, Ubuntu Server	
Internal memory type *	DDR5-SDRAM	Compatible operating systems *	
Memory clock speed	4800 MHz	Power	
Memory layout (slots x size)	1 x 32 GB	Redundant power supply (RPS) support *	✓
<b>Storage</b>		Power supply *	1800 W
Optical drive type *	✗	<b>Operational conditions</b>	
<b>Graphics</b>		Operating temperature (T-T)	5 - 45 °C
Maximum graphics card memory	16 MB	Storage temperature (T-T)	-40 - 60 °C
<b>Network</b>		Operating relative humidity (H-H)	8 - 90%
Ethernet LAN	✓	Storage relative humidity (H-H)	8 - 90%
Cabling technology	10/100/1000Base-T(X)	Operating altitude	0 - 3050 m
Ethernet interface type	Gigabit Ethernet	<b>Weight &amp; dimensions</b>	
<b>Ports &amp; interfaces</b>		Width	445 mm
Ethernet LAN (RJ-45) ports *	1	Depth	766 mm
USB 2.0 ports quantity	1	Height	87 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4	<b>Design</b>	
VGA (D-Sub) ports quantity	1	Chassis type *	Rack (2U)

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-FEB-2025. Prints or copies of Information are only valid on the printed Publication date