

LG 55UM5N-H Signage Display Digital signage flat panel 139.7 cm (55") Wi-Fi 500 cd/m² 4K Ultra HD Black WebOS 24/7

Brand: LG Product code: 55UM5N-H

Product name: 55UM5N-H

- Resolution: 3,840 x 2,160 (UHD)
- Brightness (Typ.): 500 nit
- Surface Treatement (Haze): 28 %
- Bezel: 12.4 mm (T/B), 11.4 mm (R/L)

- Interface : HDMI(3) / DP / USB 2.0 / RS232C / RJ45 / Audio / IR

- webOS Smart Platform

55" UHD 3840 x 2160, webOS, HDMI(3) / DP / USB 2.0 / RS232C / RJ45 / Audio / IR, 1237 x 710 x

57.7mm, 14.2 kg, Black

LG 55UM5N-H. Product design: Digital signage flat panel. Display diagonal: 139.7 cm (55"), Display resolution: 3840 x 2160 pixels, Display brightness: 500 cd/m², HD type: 4K Ultra HD. Wi-Fi. Operating

hours (hours/days): 24/7. Operating system installed: WebOS. Product colour: Black





Display		Performance	
Panel type LED backlight LED backlighting type Display diagonal * Display resolution * Display brightness * HD type *	light lighting type lighting type liagonal * 139.7 cm (55") 3840 x 2160 pixels rightness * 500 cd/m² 4K Ultra HD een * time 8 ms ratio (typical) ratio (dynamic) lingle, horizontal lingle, vertical umber of colours 1.07 billion colours 50000 h	Purpose * Operating hours (hours/days) HDCP Automatic brightness control International Protection (IP) code HDCP version Power	Commercial 24/7 IP5X 1.4/2.2
Touchscreen * Response time Contrast ratio (typical) Contrast ratio (dynamic) Viewing angle, horizontal Viewing angle, vertical Display number of colours Panel life		Power consumption (typical) * Power consumption (standby) * Power consumption (max) Energy efficiency class (SDR) AC input voltage AC input frequency Heat dissipation	130 W 0.5 W 180 W G 100 - 240 V 50/60 Hz 444 BTU/h
Native refresh rate		Computer system	
Haze rate Colour gamut	28% 95%	Internal memory Operating system installed	16 GB WebOS
Ports & interfaces		Operating system version	webOS 6.0
HDMI ports quantity * HDMI input ports quantity HDMI output ports quantity DisplayPorts quantity * USB port *	4 3 1 1	Weight & dimensions Display width Display depth Display height Display weight	1237 mm 57.7 mm 710 mm 14.2 kg
USB ports quantity	1	Packaging data	
SB version 2.0 ISB connector type USB Type-A thernet LAN * ✓ thernet LAN (RJ-45) ports 1	Package width Package depth Package height Package weight	1360 mm 162 mm 810 mm 18.9 kg	
Wi-Fi *	✓	Packaging content	
RS-232C	•	Remote control included	✓
Remote (IR) input	1	Batteries included	✓
Audio		Cables included	Phone, Power
Built-in speaker(s) *	✓		

Design		Operational conditions	
Product design * Placement supported *	Digital signage flat panel Indoor	Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 10 - 80%
Orientation Product colour *	Horizontal/Vertical Black	Features	
VESA mounting * Panel mounting interface	✓ 300 x 300 mm	Heat dissipation (max) Other features	614 BTU/h
Bezel width (bottom) Bezel width (side) Bezel width (top)	1.24 cm 1.14 cm 1.24 cm	Audio output Power consumption (PowerSave) Plug and Play	1 91 W

