

MPN: MO-10059

SFP 155 Mbps, SMF, 20 km, LC, DDMI support, Compatible with Extreme networks 10059

Micro-Optics products provide seamless connectivity for all your current and future network hardware needs.

- ****100% Extreme networks Compatible****



Specifications

| | | |
|------------------------|---|------------------------|
| Features | Brand compatibility | Extreme Networks |
| | Certification | MSA |
| | Compatible products | Extreme networks 10059 |
| | Easy to install | Y |
| | Form factor | SFP |
| | Hot-Plug support | Y |
| | Plug and Play | Y |
| | RoHS compliance | Y |
| Operational conditions | Operating relative humidity (H-H) | 10 - 80 % |
| | Operating temperature (T-T) | 0 - 70 °C |
| | Storage relative humidity (H-H) | 10 - 85 % |
| | Storage temperature (T-T) | -40 - 85 °C |
| Package dimensions | Gross Weight (Package, kg) | 0.02 kg |
| Packaging data | Number of products included | 1 pc(s) |
| Performance | Auto MDI/MDI-X | Y |
| | Cabling technology | 100BASE-BX10-U |
| | Digital Diagnostics Monitoring (DDM) | Y |
| | Fiber cable diameters supported (core/cladding) | 9/125 µm |
| | Fiber optic connector | LC |
| | Fiber ports quantity | 1 |
| | Interface type | SFP |
| | Maximum data transfer rate | 155 Mbit/s |
| | Maximum transfer distance | 20000 m |

| | | |
|---------------------------|--|-------------|
| Performance | Multi-mode fiber (MMF) supported | N |
| | Rx wavelength (min) | 1550 nm |
| | SFP transceiver standard | BX |
| | SFP transceiver type | Fiber optic |
| | Single-mode fiber (SMF) supported | Y |
| | Tx wavelength (min) | 1310 nm |
| | Wavelength | 1310 nm |
| Product dimensions | Net Weight (Product, kg) | 0.01 kg |
| | Product Depth | 5.65 cm |
| | Product Height | 0.85 cm |
| | Product Width | 1.34 cm |
| Vendor information | Brand Name | MicroOptics |
| | Warranty | 3 Year(s) |

Other images

