

Lenovo ThinkSystem SR630 V3 palvelin Teline (1U) Intel® Xeon® Gold 5415+ 2,9 GHz 32 GB DDR5-SDRAM 1100 W



Tuotemerkki : Lenovo Tuoteperhe: ThinkSystem Tuotekoodi: 7D73A02YEA

Tuotteen nimi: SR630 V3

Lenovo ThinkSystem SR630 V3. Suoritinperhe: Intel® Xeon® Gold, Prosessorin taajuus: 2,9 GHz, Prosessorimalli: 5415+. Sisäinen muisti: 32 GB, Sisäisen muistin tyyppi: DDR5-SDRAM, Muistin sijoittelu (paikat x koko): 1 x 32 GB. Virtalähde: 1100 W, Vikasietoisen virtalähteen tuki (RPS). Alustatyyppi: Teline (1U)

Processor		Graphics	
Processor manufacturer * Processor family * Processor model * Processor frequency * Processor boost frequency Processor cores Processor cache Number of processors installed Maximum number of SMP processors	Intel Intel® Xeon® Gold 5415+ 2.9 GHz 4.1 GHz 8 22.5 MB 1	Maximum graphics card memory	16 MB
		Ports & interfaces	
		Ethernet LAN (RJ-45) ports * USB 2.0 ports quantity USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity VGA (D-Sub) ports quantity	1 2 3 1
		Design	
		Chassis type *	Rack (1U)
Memory		Performance	
Internal memory * Internal memory type * Memory slots ECC Memory clock speed	32 GB DDR5-SDRAM 32x DIMM ✓ 4800 MHz 1 x 32 GB 8.19 TB	Performance management Trusted Platform Module (TPM) Trusted Platform Module (TPM) version	XClarity Controller Platinum ✓ 2.0
		Software	
			Misses of Windows Comes Dad Hat
Memory layout (slots x size) Maximum internal memory *		Compatible operating systems *	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi,
Maximum internal memory * Storage	8.19 TB	Compatible operating systems *	Enterprise Linux, SUSE Linux
Maximum internal memory * Storage RAID support *	8.19 TB	Compatible operating systems * Power	Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi,
Maximum internal memory * Storage	8.19 TB		Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi,
Maximum internal memory * Storage RAID support * RAID levels	8.19 TB	Power Redundant power supply (RPS) support * Power supply *	Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi, Ubuntu Server
Maximum internal memory * Storage RAID support * RAID levels Supported RAID controllers Hot-swap Optical drive type *	8.19 TB	Power Redundant power supply (RPS) support * Power supply * Number of redundant power	Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi, Ubuntu Server
Maximum internal memory * Storage RAID support * RAID levels Supported RAID controllers Hot-swap	8.19 TB O, 1, 5, 6, 10, 50, 60 9350-8i	Power Redundant power supply (RPS) support * Power supply * Number of redundant power supplies supported	Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi, Ubuntu Server
Maximum internal memory * Storage RAID support * RAID levels Supported RAID controllers Hot-swap Optical drive type *	8.19 TB	Power Redundant power supply (RPS) support * Power supply * Number of redundant power	Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi, Ubuntu Server

