## Lenovo ThinkSystem SR650 V2 palvelin 0 GB Teline ( 2U ) Intel® Xeon Silver 4309Y 2,8 GHz 32 GB DDR4-SDRAM 1100 W



Tuotemerkki : Lenovo

Tuoteperhe: ThinkSystem

Tuotekoodi: 7Z73A0AAEA

Tuotteen nimi : SR650 V2

Lenovo ThinkSystem SR650 V2. Suoritinperhe: Intel® Xeon Silver, Prosessorin taajuus: 2,8 GHz, Prosessorimalli: 4309Y. Sisäinen muisti: 32 GB, Sisäisen muistin tyyppi: DDR4-SDRAM, Muistin sijoittelu (paikat x koko): 1 x 32 GB. Kokonaistallennuskapasiteetti: 0 GB. Ethernet LAN, Kaapelitekniikka: 10/100/1000Base-T(X). Virtalähde: 1100 W, Vikasietoisen virtalähteen tuki (RPS). Alustatyyppi: Teline ( 2U)

Processor		Ports & interfaces	
Processor manufacturer * Processor family *	Intel Intel Xeon Silver	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity VGA (D-Sub) ports quantity	4
Processor model *	4309Y		1
Processor frequency *	2.8 GHz	Expansion slots	
Processor boost frequency Processor cache	3.6 GHz 12 MB	PCI Express x8 slots	2
Number of processors installed	1	PCI Express x16 slots	1
Maximum number of SMP	-	Design	
processors	2	Chassis type *	Rack (2U)
Memory		Product colour	Black, Stainless steel
Internal memory *	32 GB	Rack mounting	1
Internal memory type *	DDR4-SDRAM	Redundant fans support	<ul> <li>Image: A second s</li></ul>
Memory slots	32x DIMM	Performance	
ECC	1	Performance management	XClarity Standard
Memory clock speed	3200 MHz	Trusted Platform Module (TPM)	1
Memory layout (slots x size)	1 x 32 GB	Trusted Platform Module (TPM)	2.0
Storage		version	2.0
Total storage capacity *	0 GB	Software	
RAID support *	✓		Microsoft Windows Server, Red Hat
RAID levels	0, 1, 5, 6, 10, 50, 60	Compatible operating systems *	Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi
Supported RAID controllers	930-8i 2GB	Power	
Optical drive type *	×		
Internal drive bays	8	Redundant power supply (RPS) support *	1
Graphics		Power supply *	1100 W
Maximum graphics card memory	16 MB	Number of redundant power	2
Network		supplies supported Number of redundant power	
Wake-on-LAN ready	1	supplies installed	1
Ethernet LAN	1	Power supply input voltage	220 V
Cabling technology	10/100/1000Base-T(X)	Weight & dimensions	
Ethernet interface type	Gigabit Ethernet	Width	445 mm
Ports & interfaces		Depth	764 mm
USB 2.0 ports quantity	1	Height	87 mm





889488771172

0889488771172

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.