

Lindy 5m DP to HDMI Adapter Cable with HDR

Brand: Lindy Product code: 40928

Product name: 5m DP to HDMI Adapter Cable with HDR

- Connect a DisplayPort equipped device to a 4K HDMI display or projector
- Supports high quality resolutions up to 4K@60hz
- High Dynamic Range support provides deeper blacks, brighter whites and a wider colour gamut
- Active chipset for enhanced compatibility with various graphic cards
- 2 year warranty

5m DP to HDMI Adapter Cable with HDR

Lindy 5m DP to HDMI Adapter Cable with HDR. Cable length: 5 m, Connector 1: DisplayPort, Connector 2: HDMI Type A (Standard). Compliance certificates: CE, Federal Communications Commission (FCC), REACH, RoHS, UKCA, Certification: California Proposition 65. Cable diameter: 5 mm, Connector 1 dimensions (WxDxH): $36 \times 20 \times 7.5$ mm, Connector 2 dimensions (WxDxH): $45.1 \times 21.8 \times 12.2$ mm. Package type: Polybag. Quantity per pack: 1 pc(s)





Features		Features	
Connector 1 form factor	Straight	Cable type	Round cable
Connector 2 form factor	Straight	Connector housing material	Acrylonitrile butadiene styrene
Connector contacts plating	Gold	, and the second	(ABS)
Cable length *	5 m	Connector material	Gold
Connector 1 *	DisplayPort	AWG wire size	32
Connector 2 *	HDMI Type A (Standard)	Cable shielding	Copper braid
Connector 1 gender *	Male	Operational conditions	
Connector 2 gender *	Male	Operating temperature (T-T)	-20 - 70 °C
HDMI version	2.0	Storage temperature (T-T)	-25 - 85 °C
DisplayPort version	1.2	Certificates	
High Dynamic Range (HDR) supported	✓		CE, Federal Communications
Maximum resolution	4096 x 2160 pixels	Compliance certificates	Commission (FCC), REACH, RoHS, UKCA
Supported graphics resolutions	4096 x 2160	Certification	California Proposition 65
Maximum refresh rate	60 Hz		Camerina rioposicioni de
Refresh rate at maximum resolution		Sustainability	
Bend radius (min)	6 cm	Sustainability compliance	✓
Product colour Conductor material	Black Tinned copper -12dB@825-2475MHz -20dB@	Weight & dimensions	
Conductor material		Cable diameter	5 mm
Nominal attenuation	2475-4125MHz	Connector 1 dimensions (WxDxH)	36 x 20 x 7.5 mm
	-25dB@4125-5100MHz	Connector 2 dimensions (WxDxH)	45.1 x 21.8 x 12.2 mm
Jacket material	Polyvinyl chloride (PVC)	Packaging data	
		Package type	Polybag
		Packaging content	
		Quantity per pack	1 pc(s)
		Logistics data	
		Warranty period	2 year(s)



4002888409285

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.