Lindy 70m Cat.6 HDMI 4K60, USB and Audio KVM Extender

Brand : Lindy

Product code: 39383

Product name : 70m Cat.6 HDMI 4K60, USB and Audio KVM Extender

- Extends HDMI and USB HID signals up to 70m using a single Cat.6 cable
- Supports HDMI resolutions up to 4K@60Hz 4:4:4 8bit with HDR
- EDID management and HDMI loop-out port to connect one additional display on the transmitter
- Supports PoC (Power over Cable), requiring a power supply connection from only one side of the installation
- 2 year warranty

70m Cat.6 HDMI 4K60, USB and Audio KVM Extender
Lindy 70m Cat.6 HDMI 4K60, USB and Audio KVM Extender. Type: Transmitter & receiver, Connectivity technology: Wired, Maximum transfer distance: 70 m. Transmitter video port type: HDMI, Transmitter local video port type: HDMI, Transmitter local keyboard/mouse port type: USB. Receiver local video port type: HDMI, Receiver local keyboard/mouse port type: USB. USB port type: USB Type-A/USB Type-B. Input current: 1 A, DC voltage: 12 V

Features

Type *	Transmitter & receiver
Connectivity technology *	Wired
Maximum transfer distance	70 m
Cable types supported	Cat6
Maximum digital resolution	3840 x 2160 pixels
Maximum refresh rate	30 Hz
Product colour	Black
Material	Metal
LED indicators	✔
Number of transmitters included	1

Transmitter

Transmitter video port type	HDMI
Transmitter local video port	✔
Transmitter local video port type	HDMI
Transmitter local keyboard/mouse port type	USB
RJ-45 ports quantity (transmitter)	1

Receiver

Receiver local video port type	HDMI
Receiver local keyboard/mouse port type	USB
RJ-45 ports quantity (receiver)	1
Receiver local video ports quantity	1

Ports & interfaces

USB port type	USB Type-A/USB Type-B
HDMI version	2.0
USB 1.1 ports quantity	3

Power

DC-in jack	✔
DC voltage	12 V

Weight & dimensions

Transmitter width	9 cm
Transmitter depth	6.8 cm
Transmitter height	2.2 cm
Transmitter weight	560 g
Receiver width	9 cm
Receiver depth	6.8 cm
Receiver height	2.2 cm
Receiver weight	560 g

Packaging data

Package width	215 mm
Package depth	135 mm
Package height	75 mm
Package weight	740 g

Packaging content

AC adapter included	✔
Cables included	USB
Manual	✔
Mounting bracket(s) included	✔
Included power plug types	AU, EU, UK, US

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 90%

Power

Input current	1 A

Operational conditions

Storage relative humidity (H-H)	20 - 90%

Sustainability

Sustainability compliance	✔

Other features

Supported video modes	2160p
Bandwidth	18 Gbit/s
Compliance certificates	Federal Communications Commission (FCC), UKCA, CE, REACH, RoHS

4002888393836