



BenQ SH753P Standard throw projector 5000 ANSI lumens DLP 1080p (1920x1080) 3D White

Brand : BenQ

Product code: 9H.JGJ77.2JE

Product name : SH753P

5000 ANSI lumens, 1080P (1920x1080), 30-bit (1.07 billion colors), AC 100 to 240 V, 50/60 Hz
BenQ SH753P. Projector brightness: 5000 ANSI lumens, Projection technology: DLP, Projector native resolution: 1080p (1920x1080). Light source type: Lamp, Service life of light source: 2500 h, Service life of light source (economic mode): 3500 h. Focal length range: 20.7 - 31.05 mm, Aperture range (F-F): 2.42 - 2.97, Throw ratio: 1.39 - 2.09. Video colour modes: Presentation, Vivid. Serial interface type: RS-232



Projector		Network	
Contrast ratio (dynamic)	13000:1	Smart TV *	✗
Projector brightness *	5000 ANSI lumens	Ethernet LAN *	✓
Projection technology *	DLP	Ethernet LAN (RJ-45) ports	1
Projector native resolution *	1080p (1920x1080)	Wi-Fi *	✗
Contrast ratio (typical) *	13000:1	Storage	
Native aspect ratio *	16:9	Card reader integrated *	✗
Number of colours	1.07 billion colours	Features	
Horizontal scan range	15 - 102 kHz	Noise level (economic mode)	31 dB
Vertical scan range	23 - 120 Hz	Preset modes	Infographic
Keystone correction, horizontal	-30 - 30°	Noise level *	36 dB
Keystone correction, vertical	-30 - 30°	Multimedia	
Light source		Built-in speaker(s) *	✓
Light source type *	Lamp	RMS rated power	10 W
Service life of light source *	2500 h	Design	
Service life of light source (economic mode)	3500 h	Market positioning *	Business
Lens system		Product type *	Standard throw projector
Focal length range	20.7 - 31.05 mm	Product colour *	White
Aperture range (F-F)	2.42 - 2.97	Display	
Throw ratio	1.39 - 2.09	Built-in display *	✓
Offset	115%	Power	
Video		Power source *	AC
Full HD *	✓	Power consumption (typical) *	365 W
3D *	✓	Power consumption (standby) *	0.5 W
Video colour modes	Presentation, Vivid	AC input voltage	100 - 240 V
Ports & interfaces			
USB 2.0 ports quantity	1		

Ports & interfaces		Operational conditions	
Serial interface type *	RS-232	Operating temperature (T-T)	0 - 40 °C
PC in (D-Sub)	✓	Weight & dimensions	
VGA (D-Sub) ports quantity *	1	Width	314 mm
HDMI ports quantity *	2	Depth	233 mm
Composite video in *	1	Height	117 mm
DVI port *	✗	Weight *	3.3 kg
Packaging content			
Remote control included *		✓	
3D glasses included		✓	
Other features			
Security updates end date		31/12/2026	



4718755092909

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-FEB-2025. Prints or copies of Information are only valid on the printed Publication date