


BenQ LH856UST Ultra short throw projector 3500 ANSI lumens DLP 1080p (1920x1080) 3D Black, White

Brand : BenQ Product code: 9H.JS177.24E

Product name: LH856UST







Projector		Ports & interfaces	
Smart projector * Projector brightness * Projection technology * Projector native resolution * Contrast ratio (typical) * Native aspect ratio * Number of colours Horizontal scan range Vertical scan range Keystone correction, horizontal 3500 ANSI lumens DLP 1080p (1920x1080) 3000000:1 10:9 10.7 billion colours 15 - 135 kHz 23 - 120 Hz	×	DVI port *	×
	DLP 1080p (1920x1080) 3000000:1 16:9 1.07 billion colours 15 - 135 kHz 23 - 120 Hz	Network	
		Smart TV *	x
		Ethernet LAN *	✓
		Ethernet LAN (RJ-45) ports	1
		Wi-Fi *	X
		Storage	
		Card reader integrated *	X
Keystone correction, vertical	-15 - 15°	Features	
Light source		Interactive *	x
Light source type * Service life of light source *	Laser 20000 h	Noise level (economic mode)	32 dB
		Noise level *	34 dB
Service life of light source (economic mode)	38000 h	Multimedia	
Lens system		Built-in speaker(s) *	✓
Fixed focal length	5.1 mm 2.5	RMS rated power Number of built-in speakers	10 W 2
F-number (relative aperture)		Design	2
Throw ratio	0.33	Market positioning *	Education
Offset	124.6%	Product type *	Ultra short throw projector
Video		Product colour *	Black, White
Full HD *	✓	Display	
3D*	✓ CAO :: 400 (VCA) 2040 :: 2160	Built-in display *	x
Supported graphics resolutions	640 x 480 (VGA), 3840 x 2160	Power	
Ports & interfaces	E 11	Power source *	AC
HDMI connector type	Full-size		

Ports & interfaces		Power	
HDMI version USB 2.0 ports quantity USB 2.0 Type-A ports quantity USB 2.0 Type-B ports quantity Audio (L/R) in * Audio (L/R) out Microphone in Serial interface type * PC in (D-Sub) VGA (D-Sub) ports quantity * HDMI ports quantity *	2.0b 2 1 1 1 1 1 2 RS-232 2 2	Power consumption (typical) * Power consumption (standby) * AC input voltage AC input frequency Cord length	170 W 0.5 W 100 - 240 V 50/60 Hz 3 m
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Weight & dimensions	
		Width Depth Height Weight *	317.2 mm 208 mm 376.4 mm 6.5 kg
		Packaging content	
		Remote control included * Batteries included Mounting brackets included AC adapter included	* * * *
		Other features	
		Security updates end date	31/12/2026





4718755091353

0840046048952



840046048952

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.