

be quiet! Pure Power 12 M virtalähdeyksikkö 850 W 20+4 pin ATX ATX musta

Tuotemerkki : be quiet!

Tuotekoodi: BN344

Tuotteen nimi : Pure Power 12 M

be quiet! Pure Power 12 M. Kokonaisteho: 850 W, AC-syöttöjännite: 100 - 240 V, Huipputeho: 900 W. Emolevyn virtaliitin: 20+4 pin ATX, Emolevyn virtapiuhan pituus: 55 cm, SATA-virtakaapelin pituus: 500,600,650,800,950 mm. Tarkoitus: PC, Virransyöttöyksikön mitat: ATX, 80 PLUS certification: 80 PLUS Gold. Tuotteen väri: musta, Jäähdytyksen tyyppi: Aktiivinen, Tuulettimen halkaisija: 12 cm. Sisältää johdot: PATA, PCIe, Peripheral (Molex), SATA



Power		Ports & interfaces	
Total power *	850 W	Cabling type	Fully-Modular
Peak power	900 W	Performance	
AC input voltage *	100 - 240 V	80 PLUS certification *	80 PLUS Gold
AC input frequency	50 - 60 Hz	Purpose *	PC
Input current	12 / 6 A	Power supply unit (PSU) form factor *	ATX
Power factor	0.98	ATX version	3.0
Power Factor Correction (PFC) type	Active	EPS version	2.92
Combined power (+3.3V)	120 W	Noise level	25.7 dB
Combined power (+12V)	850 W	Mean time between failures (MTBF)	100000 h
Combined power (+5V)	120 W	Design	
Combined power (-12V)	3.6 W	Product colour	Black
Combined power (+5Vsb)	15 W	Cooling type	Active
Max output current (+3.3V)	22 A	Fan diameter	12 cm
Max output current (+12V)	70.9 A	Number of fans	1 fan(s)
Max output current (+12V1)	40 A	Fan location	Top
Max output current (+12V2)	36 A	On/off switch	✓
Max output current (+5V)	22 A	Operational conditions	
Max output current (-12V)	0.3 A	Operating temperature (T-T)	0 - 40 °C
Max output current (+5Vsb)	3 A	Packaging content	
Efficiency	93.2%	Cables included	PATA, PCIe, Peripheral (Molex), SATA
Power Good signal delay range	100 - 150 ms	Certificates	
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit	Compliance certificates	RoHS
Ports & interfaces		Weight & dimensions	
Motherboard power connector *	20+4 pin ATX	Width	160 mm
Motherboard power cable length	55 cm	Depth	150 mm
Number of SATA power connectors	6	Height	86 mm
Number of PATA power connectors	2	Packaging data	
SATA power cable length	500,600,650,800,950 mm	Package type	Box
Peripheral (Molex) power connectors (4-pin) *	1	Technical details	
Peripheral (Molex) power cable length	550 mm	Sustainability compliance	✓
EPS power connector (8-pin)	✓		
EPS power connector (4+4 pin)	✓		

Ports & interfaces		Technical details	
PCI Express power connectors (6+2 pin)	4	Sustainability certificates	ENERGY STAR, ErP
ATX power connector (20+4 pin)	✓	Logistics data	
PCI Express connector	✓	Warranty period	10 year(s)
		Other features	
		Screws included	✓
		Number of screws	5
		Cable ties included	✓
		Noise level (silent mode, <30%)	9.4 dB
		Noise level (quiet mode, 50%)	9.5 dB
		Noise level (full-load mode, 100%)	25.7 dB



4260052189498

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-FEB-2025. Prints or copies of Information are only valid on the printed Publication date