Epson EcoTank ET-2864 Mustesuihku A4 5760 x 1440 DPI 33 ppm Wi-Fi

Tuotemerkki : Epson Tuoteperhe: EcoTank Tuotekoodi: C11CJ67432

Tuotteen nimi: ET-2864

Epson EcoTank ET-2864. Tulostustekniikka: Mustesuihku, Tulostus: Väritulostus, Suurin resoluutio: 5760 x 1440 DPI, Tulostusnopeus (väri, normaalilaatu, A4/US Letter): 15 ppm. Kopiointi: Värikopiointi. Skannaus: Väriskannaus, Optinen skannauserottelutarkkuus: 1200 x 2400 DPI. Suurin ISO A-luokan paperikoko: A4. Wi-Fi. Tuotteen väri: musta





Printing		Paper handling	
Duplex printing mode	Manual	ISO B-series sizes (B0B9)	B5, B6
Print technology *	Inkjet	ISO C-series sizes (C0C9)	C6
Printing *	Colour printing	Envelopes sizes	10, C6, DL
Duplex printing *	✓	Photo paper sizes	9x13,10x15,13x20
Maximum resolution *	5760 x 1440 DPI	Ports & interfaces	
Print speed (black, normal quality, A4/US Letter) *	33 ppm	USB port	✓
Print speed (colour, normal quality, A4/US Letter)	15 ppm	Network	
Time to first page (black, normal)	10 s	Wi-Fi *	/
Time to first page (colour, normal)	16 s	Wi-Fi Direct	✓
Borderless printing	✓	Security algorithms	64-bit WEP, 128-bit WEP, WPA-PSK, WPA-TKIP, WPA2-PSK, WPA3-SAE
Copying		Design	
Copying *	Colour copying	Product colour *	Black
Scanning		Market positioning *	Home & office
Duplex scanning *	x	Built-in display *	×
Scanning *	Colour scanning 1200 x 2400 DPI	Power	
Optical scanning resolution *		Power consumption (PowerSave)	0.7 W
Scan technology	CIS	Power consumption (copying)	12 W
Image formats supported	BMP, JPEG, PICT, PNG, TIFF	Power consumption (ready)	4.5 W
Document formats supported	PDF	Power consumption (off)	0.2 W
Fax Faxing *	· ·	Energy Star Typical Electricity Consumption (TEC)	0.15 kWh/week
raxing **	×	AC input voltage	100 - 240 V
Features		AC input frequency	50/60 Hz
Number of print cartridges * Printing colours *	4 Black, Cyan, Magenta, Yellow	System requirements	
	Sider, Cydri, Pidgerica, Tellow	Windows operating systems	✓
Input & output capacity		supported Mas operating systems supported	
Total number of input trays *	1	Mac operating systems supported	✓

Input & output capacity		System requirements	
Total input capacity * Total output capacity *	100 sheets 30 sheets	Server operating systems supported	Windows Server 2012, Windows Server 2016
Paper handling		Weight & dimensions	
Maximum ISO A-series paper size *	A4	Width	375 mm
ISO A-series sizes (A0A9) *	A4, A5, A6	Depth	347 mm
		Height	179 mm
		Weight	3.9 kg



8715946725970

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.