



Lindy 38345 AV-signaalin jatkaja AV-lähetin ja -vastaanotin musta

Tuotemerkki : Lindy

Tuotekoodi: 38345

Tuotteen nimi : 38345

Lindy 38345. Malli: AV-lähetin ja -vastaanotin, Enimmäiserottelutarkkuus: 3840 x 2160 pikseliä, Tuettut kaapelityypit: Cat6. Yhteysteknologia: Langallinen. Virtalähteen malli: AC, AC-syöttöjännite: 100 - 240 V, AC-syöttötaajuus: 50/60 Hz. Tuotteen leveys: 440 mm, Tuotteen syvyys: 200 mm, Tuotteen korkeus: 45 mm. Pakkauksen leveys: 510 mm, Pakkauksen syvyys: 401 mm, Pakkauksen korkeus: 98 mm



Features		Power	
Type *	AV transmitter & receiver	Power source type	AC
Maximum resolution *	3840 x 2160 pixels	AC input voltage	100 - 240 V
Cable types supported	Cat6	AC input frequency	50/60 Hz
Maximum transfer distance	150 m	Power requirements	60 W
High Dynamic Range (HDR) supported	✓	Operational conditions	
EDID management	✓	Operating temperature (T-T)	0 - 40 °C
HDCP pass-through	✓	Storage temperature (T-T)	-20 - 60 °C
Infrared (IR) frequency range	20 - 60 kHz	Operating relative humidity (H-H)	20 - 90%
Supported video modes	1080p	Weight & dimensions	
Bandwidth	18 Gbit/s	Width	440 mm
Audio formats supported	LPCM	Depth	200 mm
On/off switch	✓	Height	45 mm
HDCP	✓	Weight	5.31 kg
Material	Metal	Receiver dimensions (WxDxH)	140 x 65 x 18 mm
Signal-to-Noise Ratio (SNR)	90 dB	Packaging data	
HDCP version	2.2	Package width	510 mm
Product colour	Black	Package depth	401 mm
Certification	California Proposition 65	Package height	98 mm
Ports & interfaces		Package weight	6.33 kg
Connectivity technology *	Wired	Package type	Box
RJ-45 output ports	4	Packaging content	
HDBaseT port	✓	Manual	✓
HDMI in	4		
Number of HDMI outputs	5		
HDMI version	2.0		
RS-232 input ports	2		
Digital audio coaxial out	4		

Ports & interfaces		Packaging content	
Audio (L/R) out	4		4x4 HDBaseT Extender Matrix - Transmitter 4 x HDBaseT Receivers
3.5 mm (1/8-inch) in	✓		5 x IR Emitter Cable, 1.5m 5 x IR Receiver Cable, 1.5m 10 x Mounting Ears & Screws 4 x 3-Pin Terminal Block 4 x 5-Pin Terminal Block
3.5 mm (1/8-inch) out	✓	Packaging content	RS-232 Male to Female cable, 1.5m 4 x mains cables (EU, UK, US & AUS), 1.5m Lindy Manual
Audio RCA outputs	4		
Technical details			
Sustainability compliance			✓
Warranty period			2 year(s)
Compliance certificates			CE, Federal Communications Commission (FCC), REACH, RoHS, UKCA



4002888383455

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 03-FEB-2025. Prints or copies of Information are only valid on the printed Publication date