



BenQ X3100i 3300 ANSI lumenia DLP UHD 4K (3840x2160) 3D musta

Tuotemerkki : BenQ

Tuotekoodi: 9H.JS977.18E

Tuotteen nimi : X3100i

BenQ X3100i. Projektorin kirkkaus: 3300 ANSI lumenia, Projektioteknologia: DLP, Projektorin oletusresoluutio: UHD 4K (3840x2160). Valonlähteen tyyppi: LED, Valonlähteen käyttöikä: 20000 h, Valonlähteen käyttöikä (säästötila): 30000 h. Polttovälialue: 17.02 - 22.21 mm, Aukkoalue (F-F): 1,8 - 2,25, Zoomaussuhde: 1.3:1. Tuetut grafiikan erottelutarkkuudet: 640 x 480 (VGA), 3860 x 2160. Sarjaliitännän tyyppi: RS-232, HDMI/liitäntätyyppi: Täysikokoinen, HDMI-versio: 2.0b



Projector		Network	
Smart projector *	✓	Wi-Fi *	✓
Projector brightness *	3300 ANSI lumens	Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Projection technology *	DLP	Bluetooth	✓
Projector native resolution *	UHD 4K (3840x2160)	Bluetooth version	5.0
Contrast ratio (typical) *	600000:1	Storage	
Native aspect ratio *	16:9	Card reader integrated *	✗
Number of colours	1.07 billion colours	Features	
Horizontal scan range	15 - 135 kHz	Interactive *	✗
Vertical scan range	20 - 240 Hz	Noise level (economic mode)	28 dB
Light source		HDCP	✓
Light source type *	LED	Noise level *	32 dB
Service life of light source *	20000 h	Works with the Google Assistant	✓
Service life of light source (economic mode)	30000 h	AirPlay	✓
Lens system		Multimedia	
Focal length range	17.02 - 22.21 mm	Built-in speaker(s) *	✓
Aperture range (F-F)	1.8 - 2.25	RMS rated power	10 W
Zoom capability	✓	Number of built-in speakers	2
Zoom ratio	1.3:1	Design	
Throw ratio	1.15 - 1.5	Market positioning *	Gaming
Vertical lens shift range	40 - 60%	Product colour *	Black
Offset	110%	Display	
Video		Built-in display *	✗
Full HD *	✓	Power	
3D *	✓	Power source *	AC
Supported graphics resolutions	640 x 480 (VGA), 3860 x 2160		

Ports & interfaces		Power	
HDMI connector type	Full-size	Power consumption (typical) *	330 W
HDMI version	2.0b	Power consumption (standby) *	0.5 W
USB 2.0 ports quantity	1	AC input voltage	100 - 240 V
Serial interface type *	RS-232	AC input frequency	50 - 60 Hz
PC Audio out	✓	Operational conditions	
S/PDIF out port	✓	Operating temperature (T-T)	0 - 40 °C
HDMI ports quantity *	3	Weight & dimensions	
DVI port *	✗	Width	272 mm
Network		Depth	213 mm
Ethernet LAN *	✗	Height	259 mm
		Weight *	6.8 kg
		Packaging content	
		Remote control included *	✓



4718755092244

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 07-MAR-2025. Prints or copies of Information are only valid on the printed Publication date