



## DELL P2724DEB 68.6 cm (27") LCD 2560 x 1440 pixels Quad HD

Brand : DELL

Product code: DELL-P2724DEB

Product name : P2724DEB

- 68.6cm (27") Quad HD 2560 x 1440 LED IPS
  - 8ms, 16:9, 350cd/m<sup>2</sup>, 1000:1
  - USB, HDMI, DisplayPort
- 68.6cm (27") Quad HD 2560 x 1440 LED IPS, 16:9, 350cd/m<sup>2</sup>, 16.78M, 8ms, 178°/178°, 1000:1

DELL P2724DEB 68.6 cm (27") LCD 2560 x 1440 pixels Quad HD:

Connect like you're there with a 27-inch QHD IPS display built for effortless collaboration. DELL P2724DEB. Display diagonal: 68.6 cm (27"), Display technology: LCD, Display resolution: 2560 x 1440 pixels. Megapixel (approx.): 4 MP, Maximum frame rate: 60 fps. RMS rated power: 10 W. Product colour: Black, Silver, Screen shape: Flat, Panel mounting interface: 100 x 100 mm. USB version: 3.2 Gen 1 (3.1 Gen 1), USB Power Delivery up to: 90 W



Display		Computer system	
Display diagonal *	68.6 cm (27")	Computer system *	✗
Display technology *	LCD	Windows operating systems supported	Windows 10, Windows 11
Panel type	IPS	Mac operating systems supported	MacOS
LED backlight	✓	<b>Performance</b>	
Display resolution *	2560 x 1440 pixels	On Screen Display (OSD)	✓
Display brightness	350 cd/m <sup>2</sup>	HDCP	✓
HD type *	Quad HD	HDCP version	1.4
Touchscreen *	✗	<b>Power</b>	
Native aspect ratio *	16:9	Power consumption (typical)	26 W
Response time	8 ms	Power consumption (max)	210 W
Contrast ratio (typical)	1000:1	Power consumption (standby)	0.3 W
Viewing angle, horizontal	178°	AC input voltage	100 - 240 V
Viewing angle, vertical	178°	AC input frequency	50/60 Hz
Display number of colours	16.78 million colours	Energy efficiency scale	A to G
Pixel pitch	0.2331 x 0.2331 mm	Energy efficiency class (SDR) *	F
Display diagonal (metric)	68.47 cm	Energy consumption (SDR) per 1000 hours *	26 kWh
Surface hardness	3H	Power supply type	Internal
Anti-glare screen	✓	<b>Operational conditions</b>	
<b>Camera</b>		Operating temperature (T-T)	0 - 40 °C
Built-in camera	✓	Storage temperature (T-T)	-20 - 60 °C
Megapixel (approx.)	4 MP	Operating relative humidity (H-H)	10 - 80%
Maximum frame rate	60 fps	Storage relative humidity (H-H)	5 - 90%
<b>Audio</b>		<b>Weight &amp; dimensions</b>	
Built-in speaker(s)	✓	Display width	611.8 mm
Number of built-in speakers	2	Display depth	59.6 mm
RMS rated power	10 W	Display height	415.8 mm
<b>Design</b>		Display weight	5.65 kg
Product colour *	Black, Silver		
Screen shape	Flat		

Design		Weight & dimensions	
VESA mounting *	✓	Width (with stand)	611.8 mm
Panel mounting interface	100 x 100 mm	Depth (with stand)	230 mm
Bezel width (bottom)	1.72 cm	Height (with stand)	440.8 mm
Bezel width (side)	7.52 mm	Weight (with stand)	8.27 kg
Bezel width (top)	3.84 cm	<b>Packaging data</b>	
Height adjustment	✓	Package weight	11.3 kg
Height adjustment	15 cm	<b>Packaging content</b>	
Pivot	✓	Stand included	✓
Pivot angle	-90 - 90°	Remote control included	✗
Swivelling	✓	Stylus pen	✗
Swivel angle range	-45 - 45°	Power adapter included	✓
Tilt angle range	-5 - 21°	Cables included	DisplayPort, USB Type-A to USB Type-B, USB Type-C
<b>Ports &amp; interfaces</b>		<b>Sustainability</b>	
HDMI ports quantity *	1	Sustainability certificates	ENERGY STAR, TCO
HDMI version	1.4	<b>Network</b>	
DVI port *	✗	Ethernet LAN *	✓
DisplayPorts quantity	1	Ethernet LAN (RJ-45) ports	1
USB ports quantity	6	Wi-Fi *	✗
USB version	3.2 Gen 1 (3.1 Gen 1)	<b>Technical details</b>	
USB 2.0 Type-B ports quantity	1	Compliance certificates	RoHS
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3	<b>Carbon footprint</b>	
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1	Total carbon footprint (kg of CO2e)	604
Number of USB Type-B upstream ports quantity	1	Total carbon emissions, standard deviation (kg of CO2e)	157
Number of USB Type-C upstream ports quantity	1	Carbon emissions, manufacturing (kg of CO2e)	334
USB Type-A downstream ports quantity	3	Carbon emissions, logistics (kg of CO2e)	58
USB Type-C downstream ports quantity	1	Carbon emissions, energy usage (kg of CO2e)	206
Microphone in	✓	Carbon emissions, end-of-life (kg of CO2e)	7
USB port *	✓	Total carbon emissions, w/o use phase (kg of CO2e)	398
USB Type-C DisplayPort Alternate Mode	✓	PAIA version	1.3.2
USB Power Delivery (USB PD)	✓		
USB Power Delivery up to	90 W		



5397184657065

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-DEC-2024. Prints or copies of Information are only valid on the printed Publication date