



APC GVSUPS15KB4HS UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 15 kVA 15000 W

Tuotemerkki : APC

Tuotekoodi: GVSUPS15KB4HS

Tuotteen nimi : GVSUPS15KB4HS

APC GVSUPS15KB4HS. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 15 kVA, Lähtöteho: 15000 W. Pistorasian tyypit: Hard Wire 3-wire (1PH + N + G), Hard Wire 4-wire (3PH + G). Akkuteknologia: Sealed Lead Acid (VRLA), Akun jännite: 480 V. Kotelo: Tower, Tuotteen väri: Valkoinen, Näytön tyyppi: LCD. Sertifiointi: CSA C22.2 NO. 107.3, EN/IEC 62040-1, EN/IEC 62040-2, EN/IEC 62040-3, IEC 60721-4-2 Level 2M2, UL...



Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Tower
Output power capacity *	15 kVA	Product colour *	White
Output power *	15000 W	Display type	LCD
Waveform *	Sine	International Protection (IP) code	IP20
Input operation voltage (min) *	340 V	Operational conditions	
Input operation voltage (max) *	460 V	Operating temperature (T-T)	0 - 40 °C
Input frequency *	40/70 Hz	Storage temperature (T-T)	-15 - 40 °C
Output operation voltage (min)	380 V	Operating relative humidity (H-H)	0 - 95%
Output operation voltage (max)	415 V	Storage relative humidity (H-H)	0 - 95%
Output frequency	50/60 Hz	Operating altitude	0 - 1000 m
Maximum current	27 A	Non-operating altitude	0 - 3000 m
Number of input phases	3	Certificates	
Number of output phases	3	Certification	CSA C22.2 NO. 107.3, EN/IEC 62040-1, EN/IEC 62040-2, EN/IEC 62040-3, IEC 60721-4-2 Level 2M2, UL 1778 5th edition
Input power factor	0.99	Packaging content	
Crest factor	2.5:1	Quick installation guide	✓
ECO mode	✓	Weight & dimensions	
Output voltage Total Harmonic Distortion (THD)	3%	Width	521 mm
Input current Total Harmonic Distortion (THD)	3%	Depth	847 mm
Noise level	55 dB	Height	1485 mm
Power protection features	Overload, Short circuit	Weight	330 kg
Audible alarm(s)	✓		

Ports & interfaces		Packaging data	
AC outlet types	Hard Wire 3-wire (1PH + N + G), Hard Wire 4-wire (3PH + G)	Package width	640 mm
SmartSlot	✓	Package depth	990 mm
Battery		Package height	1680 mm
Battery technology	Sealed Lead Acid (VRLA)	Package weight	360 kg
Battery voltage	480 V	Logistics data	
		Harmonized System (HS) code	85078000



0731304406747



731304406747



5054444446103

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.