

DELL UltraSharp U2424H_WOST computer monitor 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Black, Silver

Brand : DELL

Product family: UltraSharp

Product code: DELL-U2424HWOS

Product name : U2424H_WOST

- 60.5cm (23.8") Full HD 1920 x 1080 Edge LED IPS

- 8ms, 16:9, 250cd/m², 1000:1

- USB, HDMI, DisplayPort

60.5cm (23.8") Full HD 1920 x 1080 Edge LED IPS, 16:9, 250cd/m², 16.7M, 8ms, 178°/178°, 1000:1

DELL UltraSharp U2424H_WOST computer monitor 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Black, Silver:

Experience improved visual comfort, enhanced productivity and extensive connectivity with this monitor certified by TÜV for 4-star eye comfort.

DELL UltraSharp U2424H_WOST. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 3.2 Gen 2 (3.1 Gen 2). VESA mounting, Height adjustment. Product colour: Black, Silver





| Display | | Ports & interfaces | |
|--------------------------------|--|-----------------------------------|---------------|
| Display diagonal * | 60.5 cm (23.8") | HDCP version | 1.4 |
| Display resolution * | 1920 x 1080 pixels | AC (power) in | 1 |
| HD type * | Full HD | Network | |
| Native aspect ratio * | 16:9 | Wi-Fi | × |
| Display technology * | LCD | | ^ |
| Panel type * | IPS | Ergonomics | |
| Backlight type | Edge LED | VESA mounting * | 1 |
| Touchscreen * | × | Panel mounting interface | 100 x 100 mm |
| Display brightness (typical) | 250 cd/m ² | Cable lock slot * | 1 |
| Response time * | 8 ms | Cable lock slot type | Kensington |
| Anti-glare screen | | Height adjustment * | 1 |
| Screen shape * | Flat | Height adjustment | 15 cm |
| | 640 x 480 (VGA), 720 x 400, 720 x 480, 800 x 600 (SVGA), 1024 x 768 | Pivot | 1 |
| Supported graphics resolutions | (XGA), 1152 × 864 (XGA+), 1280 × 1024 (SXGA), 1280 × 720 (HD 720), 1600 × 900, 1920 × 1080 (HD 1080) | Pivot angle | -90 - 90° |
| | | Swivelling | ✓ |
| Supported video modes | 480p, 576p, 720p, 1080i, 1080p | Swivel angle range | -45 - 45° |
| Contrast ratio (typical) * | 1000:1 | Tilt adjustment | 1 |
| Maximum refresh rate * | 120 Hz | Tilt angle range | -5 - 21° |
| Viewing angle, horizontal | 178° | On Screen Display (OSD) | 1 |
| Viewing angle, vertical | 178° | Power | |
| Display number of colours * | 16.7 million colours | Energy efficiency class (SDR) * | F |
| Response time (fast) | 5 ms | Energy efficiency class (HDR) * | Not available |
| Pixel pitch Pixel density | 0.2745 x 0.2745 mm 92.53 ppi | Energy consumption (SDR) per 1000 | 24 kWh |
| Horizontal scan range | 31 - 135 kHz | hours * | |
| Vertical scan range | 48 - 120 Hz | Power consumption (typical) * | 13.7 W |
| Viewable size, horizontal | 52.7 cm | Power consumption (standby) * | 0.5 W |
| Viewable size, vertical | 29.6 cm | Power consumption (max) | 72 W |
| | | | |

| PurpleNumber of the set of the | Display | | Power | |
|---|---------------------------|------------|---------------------------|---|
| Display diagonal (metric)60.47 cmAC input voltage100 - 240 VHigh Dynamic Range (HDR) supportedXAc input frequency50/60 HzSurface hardness3HPower supply typeInternalColour gamut stadardDCI-P3Energy efficiency scaleX to GColour gamut stadardDCI-P3Energy efficiency scaleX to GColour gamut stadardDCI-P3Energy efficiency scaleX to GColour gamut stadardDCI-P3Energy efficiency scaleX to GPerformanceQperating temperature (I-T)-20 - 60 °CMDIA G-SYNC*XOperating temperature (I-T)-20 - 60 °CAMD FreeSync *XOperating relative hunidity (H+H)5 - 80%Joe Bult in speaker(s) *XOperating relative hunidity (H+H)5 - 80%MultimediaYNon-operating altitude0 - 5000 mMultimediaXWeight 6 dimensionXBult-in speaker(s) *XWeight 6 dimension10.8 nmProduct colour *Black, SiverBezel width (side)5.8 nmProduct colour *Black, SiverBezel width (side)5.8 nmProduct colour *Slace (2.1.1 Gen 2)Stand includedXUSB type-A downstream ports quantityQuest at guidth (side)5.8 nmVB bub *usion3.2 Gen 2 (3.1 Gen 2)Stand includedXUSB type-C downstream ports quantityQuest at guidth (side)5.8 nmSiglis fortureYape-CColous includedXUSB type-C | | 60.5 cm | | 0.3 W |
| high opymamic Range (HDR) supported×AC input current input current50/60 H2 input currentSurface hardness3HPoer supply type ten rend version (Same Supply type ten rend version (Same Supply type) ten rend version (Same Supply | 5 | | • • • | |
| subported^Input current1.5 ASurface hardness3HPower supply typeinternalSurface hardness3HPower supply typeinternalColour gamut85%European Product Registry for European Produ | | | 1 5 | |
| Colour gamut standardDCI-P3 Energy efficiency scaleInterinaColour gamut85%European Product Registry for Energy Labelling (EPREL) code1391641ReformanceVOperatinal conditionsVPerformaceXOperatinal temperature (T-T) 20 - 60 °C °C0-40 °CAMD FreeSync *XStorage temperature (T-T) 20 - 60 °C0-60 °CFlicker-free technology-Storage temperature (T-T) 20 - 60 °C0-60 °CMultimediaXStorage relative humidity (H+H) 5 - 90%0-60 °CBulti-in speaker(S) *XWeight & dimensions000 ·12192 mBulti-in speaker(S) *XWeight & dimensions000 ·12192 mBulti-in speaker(S) *XWeight & dimensions0-5000 mBulti-in speaker(S) *XWeight & dimensions0-5000 mBulti-in speaker(S) *Network (SilverDeprint without stand)358.6 mmBulti-in speaker(S) *BisckWeight (without stand)352.kgProduct colour *BiackBezel width (toto)3.52 kgProduct colour *BiackSilverSilverBulti-in USB hub *-SourceSilverPorts & interfaceVSilverSilverBulti-In USB hub *-SilverSilverBulti-In USB hub *-SilverSilverBulti-In USB hub *-SilverSilverBulti-In USB hub *-SilverSilverUSB hub restore-SilverSilver <t< td=""><td></td><td>×</td><td></td><td></td></t<> | | × | | |
| Colour jamutBS% Burgen Product Registry for Energy Labeling (EPREL) codeA 0 GSKGE coverage (typical)100%Performance1591641PerformanceOperating temperature (T-T)-2.0 -6.0 °CMUDIA GSYNC*XStorage temperature (T-T)-2.0 -6.0 °CAMD FreeSync*XOperating temperature (T-T)-2.0 -6.0 °CFickker-free technology-Storage relative humidity (H+H)10.90%Low Blu Light technology-Operating atlitude0.5000 mMutimedia-Non-operating atlitude0.5000 n.212192 mBuilt-in cameraXWeight & dimensionsStale manifection (Stale (S | Surface hardness | ЗН | Power supply type | Internal |
| sRGB coverage (typical) 100% European Product Regist/ performance 1591641 Performance Operating temperature (T-T) 0 - 40 °C NVIDA G-SYNC* × Operating temperature (T-T) 0 - 60 °C AMD FreeSync* × Operating relative humidity (H-H) 10 - 80% Elicker-free technology - Operating relative humidity (H-H) 5 - 90% Low Blue Light technology - Operating altitude 5 - 90% Multimedia × Operating altitude 5 - 90% Built-in speaker(s)* X Weight & dimensions 5 - 80% Built-in camera* X Weight (without stand) 5 - 80% Product colour* Business Weight (without stand) 5 - 80% Product colour* Black, Silver Bezel width (side) 5 - 8 mm Product colour* Black Bezel width (side) 5 - 8 mm Fort bezel colour Black Bezel width (side) 5 - 8 mm Product colour* Black Bezel width (side) 5 - 8 mm Fort bezel colour S - 9 C S - 9 C S - 9 C Silver Bradin cluded X C S - 9 C Silver Bradin cluded X C S - 9 C Silver S - 9 C< | 5 | | Energy efficiency scale | A to G |
| skbs coverage (typical)JUb%Energy Labeling (Erket) CodePerformanceOperating temperature (T-T)0 - 40 °CMVIDIA G-SYNC*XStorage temperature (T-T)-20 - 60 °CAMD FreeSync*XOperating relative humidity (H-H)10 - 80%Low Blue Light technology-Operating relative humidity (H-H)10 - 80%Low Blue Light technology-Operating relative humidity (H-H)5000 mMutimedia-Non-operating altitude0 - 5000 mBuilt-in camera *XWidh (without stand)538.6 mmBeilgeDepth (without stand)538.6 mmPoint comera *BusinessWeight (without stand)496.5 mmProduc colour *Black, SilverBezel width (ide)5.8 mmProt bezel colour *Black, SilverBezel width (ide)5.8 mmProt bezel colour *BlackSilverBezel width (top)5.8 mmProt bezel colour *BlackSilverBezel width (top)5.8 mmPorts & interfaces-Stand includedXUSB hub *-SilverStand includedXUSB upstram port typeUSB Type-C downstream ports quantitySilverStand includedXUSB Type-A downstream ports quantity1Quick start guide< | - | | | 1591641 |
| NVIDIA G-SYNC*×Operating temperature (T-T)0 - 40 °CAMD FreeSync*×Storage temperature (T-T)-20 - 60 °CFlicker-free technology-Operating relative humidity (H-H)5 - 90%Low Blue Light technology-Storage relative humidity (H-H)5 - 90%Low Blue Light technology-Non-operating altitude0 - 5000 mMutimedia-Non-operating altitude0 - 5000 mBuilt-in camera *XWeight & dimensions538.6 mmBuilt-in camera *XWidth (without stand)538.6 mmPesignDepth (without stand)496.5 mm406.5 mmProduct colour *Black, SliverBezel width (side)5.8 mmProduct colour *Black, SliverBezel width (side)5.8 mmPorts & interfacesPackaging content95 mmPuts & interfacesPackaging content7Sull-lin USB hub *-Stan included×USB hub version3.2 Gen 2 (3.1 Gen 2)Cables included×USB type-A downstream ports quantityQuick sart guide-USB Type-A downstream ports quantityQuick sart guide×USB Type-A downstream ports quantity1< | | 100% | | |
| AMD FreeSynt*XStorage temperature (T.T)-20 - 60 °CFlicker-free technology✓Operating relative humidity (H-H)10 - 80%Low Blue Light technology✓Operating relative humidity (H-H)5 - 90%Low Blue Light technology✓Non-operating altitude0 - 5000 mMuttimedia×Non-operating altitude0 - 5000 mBuilt-in speaker(s) *XWeight & dimensions58.6 mmBuilt-in camera *XWidth (without stand)58.6 mmBuilt-in camera *XWeight (without stand)496.5 mmPorduct colour *Black, SilverBezel width (top)5.8 mmProduct colour *BlackBezel width (top)5.8 mmFeet colourBlackBezel width (top)5.8 mmFeet colourSilverStand includedXBuilt-in USB hub*✓Stand includedXUSB hub*J.2 Gen 2 (3.1 Gen 2)Cables includedXUSB hub*J.2 Gen 2 (3.1 Gen 2)Cables included×USB hub*J.2 Gen 2 (3.1 Gen 2)Cables included×USB hub*J.2 Gen 2 (3.1 Gen 2)Cables included×USB hup ers for superating ers for superati | Performance | | • | |
| And reesyn.APicker-Free technology✓Storage relative humidity (H-H)10 - 80%Storage relative humidity (H-H)5 - 90%Operating altitude000 mMuttimedia✓Built-in speaker(s)*XBuilt-in camera*XBuilt-in camera*XDesignMidth (without stand)Market positioning*BusinessBuik-s (SilverBezel width (side)BolkBlackBezel colourBlackBezel width (bottom)8.95 mmPert colour*BlackBuilt-in USB hub*✓SilverBezel width (side)Built-in USB hub*✓USB hub version3.2 Gen 2 (3.1 Gen 2)USB hub version3.2 Gen 2 (3.1 Gen 2)USB hub version3.2 Gen 2 (3.1 Gen 2)USB hub version1Outer 4 dumstream port typeUSB Type-CUSB Type-C upstream ports quantity1USB Type-C dumstream ports quantity31000 (SignapPort usb Type-CSustainability1100 (SignapPort usb Type-C townstream ports quantity3121 (SignapPort usb Type-C dumstream ports quantity1121 (SignapPort usb Type)1121 (SignapPort usb Type)1122 (SignapPort usb Type)1123 (SignapPort usb Type)1124 (SignapPort usb Type)1125 (SignapPort usb Type)1125 (SignapPort usb Type)1125 (SignapPort usb Type)1125 (Signap | NVIDIA G-SYNC * | × | | |
| Inclue lectimicationImage relative humidity (H-H)5 - 90% 0 perating altitude5 - 90% 0 - 5000 mMultimediaNon-operating altitude5000 - 12192 mBuilt-in camera *XWeight & dimensionsBuilt-in camera *XWidth (without stand)538.6 mmDesignVidth (without stand)538.6 mmPesignBlack, SilverBezel width (side)5.8 mmProduct colour *Black, SilverBezel width (side)5.8 mmProduct colour *Black, SilverBezel width (side)5.8 mmProt Sc interfacesSilverBezel width (side)5.8 mmPorts 6 interfacesSilverBezel width (side)5.8 mmBuilt-in USB hub *SilverStand included%USB pub version3.2 Gen 2 (3.1 Gen 2)Stand included%USB hub version3.2 Gen 2 (3.1 Gen 2)Stand included%USB hub version3.2 Gen 2 (3.1 Gen 2)Stand included%USB Type-A downstream port squantity1Power adapter included%USB Type-A downstream ports quantity1Quick start guide< | AMD FreeSync * | × | | |
| Low Blue Light technology✓Operating altitude0 - 5000 mMuttimediaNon-operating altitude0 - 5000 mBuilt-in speaker(s)*XWeight & dimensionsBuilt-in camera*XWeight & dimensionsBuilt-in camera*XWeight & dimensionsBuilt-in camera*XWeight (without stand)538.6 mmDesignDepth (without stand)496.5 mmMarket positioning*BusinessWeight (without stand)3.52 kgProduct colour*Black, SilverBezel width (side)5.8 mmFront bezel colourBlackBezel width (top)5.8 mmPorts & interfacesVStand includedXBuilt-in USB hub*✓Stand includedXUSB hub version3.2 Gen 2 (3.1 Gen 2)Cables includedXUSB supream port typeUSB Type-CStand includedXVumber of USB Type-C upstream quantity1Operating altitude×USB Type-C downstream ports quantity1Stylus included×USB Type-C downstream ports quantity1Sustainability×HDMI ports quantity1Sustainability×HDMI version1.4Sustainability certificatesENERGY STAR, TCODisplayPorts quantity1.4Sustainability certificatesENERGY STAR, TCOHDMI version1.4Sustainability certificatesENERGY STAR, TCODisplayPorts quantity1Goern't containPUC/BFRHeadphone out*×Sustai | Flicker-free technology | 1 | | |
| MuttimediaNon-operating altitude5000 + 1219 mBuilt-in speaker(s)*XWeight & dimensionsBuilt-in camera*XWidth (without stand)538.6 mmBuilt-in camera*XDepth (without stand)181.8 mmPresignBusnessHeight (without stand)3.52 kgProduct colour*BlackBezel width (side)3.52 kgFornt bezel colourBlackBezel width (top)5.8 mmFort bezel colourBlackBezel width (top)5.8 mmFort bezel colourSilverBezel width (top)5.8 mmFort bezel colourSilverBezel width (top)5.8 mmFort bezel colourSilverBezel width (top)5.8 mmFort bezel colourSilverSamonactionationationationationationationationa | Low Blue Light technology | 1 | | |
| Built-in speaker(s)*×Weight & dimensionsBuilt-in camera*×Width (without stand)538.6 mmBuilt-in camera*×Depth (without stand)181.8 mmDesignDepth (without stand)496.5 mmMarket positioning*BusinessWeight (without stand)496.5 mmProduct colour*Black, SilverBezel width (side)5.8 mmFront bezel colourBlackBezel width (side)5.8 mmFeet colourSilverBezel width (bottom)8.95 mmPorts & interfaces-Stand included×Built-in USB hub*-Stand included×USB upstream port typeUSB Type-CCables included×USB Type-C oupstream ports quantity1Power adapter included×USB Type-C downstream ports quantity1Quick start guide-USB Type-C downstream ports quantity1Sustainability compliance.HDMI *-Sustainability complianceHDMI version1.4Sustainability complianceDisplayPort version1.4Desn't containPVC/gFRHDMI version1.4Desn't containPVC/gFRHeadphone out*Headphone out*Headphone out*Headphone inXHot inHeadphone in <td>Multimedia</td> <td></td> <td></td> <td></td> | Multimedia | | | |
| Built-in camera* X Width (without stand) 538.6 mm Design Width (without stand) 538.6 mm Market positioning* Business Height (without stand) 496.5 mm Product colour* Black, Silver Bezel width (bott) 3.52 kg Front bezel colour Black Bezel width (top) 5.8 mm Feet colour Silver Bezel width (bottom) 8.95 mm Ports & interfaces Packaging content Sama S.8 mm Built-in USB hub* Scale width (bottom) 8.95 mm USB hub version 3.2 Gen 2 (3.1 Gen 2) Stand included X USB hub version 3.2 Gen 2 (3.1 Gen 2) Cables included USB Type-C downstream port type USB Type-C Cables included × USB Type-C downstream ports quantity 3 Stand included × USB Type-C downstream ports quantity Quick start guide × USB Type-C downstream ports quantity Quick start guide × USB Type-C downstream ports quantity I Statianability compliance <t< td=""><td>Built-in speaker(s) *</td><td>×</td><td></td><td>5000 12152 111</td></t<> | Built-in speaker(s) * | × | | 5000 12152 111 |
| DesignNumber of USB Type-CDesk (SilverBeack (Silver)Beack (Silver)Silver)Beack (Silver)Silver)Beack (Silver)Silver)Silver)< | | | 5 | E 29.6 mm |
| DesignHeight (without stand)496.5 mmMarket positioning *Biack, SilverHeight (without stand)3.52 kgProduct colour *Biack, SilverBezel width (side)5.8 mmFront bezel colourBlackBezel width (side)5.8 mmFeet colourSilverBezel width (top)5.8 mmPorts & interfacesPackaging content5.9 mmBuilt-in USB hub *Packaging contentUSB hub version3.2 Gen 2 (3.1 Gen 2)Stand includedXUSB upstream port typeUSB Type-CCables includedVSB type-A downstream ports quantity1Power adapter includedXUSB Type-C downstream ports quantity1Quick start guideXUSB Type-C downstream ports quantity1Sustainability complianceXHDMI ersion1.4Sustainability complianceDisplayPort version1.4Sustainability certificatesENERGY STAR, TCODisplayPort version1.4Sustainability certificatesENERGY STAR, TCODisplayPort version1.4GeneruresPoweration for the featuresHeadphone out *Sustainability certificatesENERGY STAR, TCODisplayPort version1.4GeneruresENERGY STAR, TCODisplayPort version1.4GeneruresENERGY STAR, TCODisplayPort version1.4GeneruresENERGY STAR, TCODisplayPort version1.4GeneruresENERGY STAR, TCODisplayPort version <td></td> <td>^</td> <td>. ,</td> <td></td> | | ^ | . , | |
| Market positioning*BusinessWeight (without stand)3.52 kgProduct colour *Black, SilverBezel width (side)5.8 mmFront bezel colourBlackBezel width (top)5.8 mmFeet colourSilverBezel width (top)8.95 mmPorts & interfacesPackaging contentBezel width (bottom)8.95 mmBuilt-in USB hub *Packaging content*USB type to use provide the service of the serv | - | | • • | |
| Product colourBlackBezel width (side)5.8 mmFront bezel colourBlackBezel width (top)5.8 mmFeet colourSilverBezel width (top)8.95 mmPorts & interfacesPackaging contentPackaging contentBuilt-in USB hub*Stand includedXUSB hub version3.2 Gen 2 (3.1 Gen 2)Cables includedXUSB upstream port typeUSB Type-CCables includedNumber of USB Type-C upstream quantity1Power adapter includedUSB Type-C downstream ports quantity1Remote control includedXUSB Type-C downstream ports quantity1Quick start guideHDMI *Sustainability complianceHDMI ports quantity1.4Sustainability complianceHDMI version1.4Sustainability complianceDisplayPort version1.4Desn't containPVC/BFRHeadphone out *Microphone inXPC Audio inX <td></td> <td></td> <td>5 ()</td> <td></td> | | | 5 () | |
| Feet colourBilverBezel width (top) Bezel width (tot)5.8 mm Bezel width (bottom)Ports & interfacesBezel width (bottom)8.95 mmBuilt-in USB hub *Packaging contentUSB hub version3.2 Gen 2 (3.1 Gen 2)Stand includedXUSB upstream port typeUSB Type-CCables includedAC, DisplayPort, USB Type-A to USBNumber of USB Type-C upstream ports quantity1Power adapter includedUSB Type-A downstream ports quantity3Remote control includedXUSB Type-C downstream ports quantity1Stylus includedXHDMI *Stylus includedXHDMI ports quantity1Sustainability complianceHDMI version1.4Sustainability complianceDisplayPort version1.4Sustainability certificatesENERGY STAR, TCODisplayPort version1.4CenterHeadphone out *XMicrophone inXPC Audio inXPC Audio inXBuilt-inXBuilt-inXBuilt-inXBuilt-inMicrophone inXBuilt-inMicrophone inXBuilt-inXBuilt-inXBuilt-inXBuilt-inXBuilt-inX </td <td></td> <td></td> <td>u</td> <td></td> | | | u | |
| Ports & interfaces Bezel width (bottom) 8.95 mm Built-in USB hub * / Packaging content USB hub version 3.2 Gen 2 (3.1 Gen 2) Stand included X USB upstream port type USB Type-C Cables included AC, DisplayPort, USB Type-A to USB Type-C Number of USB Type-C upstream ports quantity 1 Power adapter included USB Type-C downstream ports quantity 3 Remote control included X USB Type-C downstream ports quantity 1 Quick start guide X USB Type-C downstream ports quantity 1 Quick start guide X HDMI * / Isinability Isinability HDMI version 1.4 Sustainability compliance DisplayPort version 1.4 Sustainability certificates ENERGY STAR, TCO DisplayPort version 1.4 Desn't contain PVC/BFR Headphone out * / Meansplitty certificates ENERGY STAR, TCO DisplayPort version X Meansplitty certificates PVC/BFR Headphone out * / | | | Bezel width (top) | 5.8 mm |
| Built-in USB hub * ✓ Packaging content Built-in USB hub version 3.2 Gen 2 (3.1 Gen 2) Stand included X USB upstream port type USB Type-C Cables included AC, DisplayPort, USB Type-A to USB Type-C upstream Number of USB Type-C upstream ports quantity 1 Power adapter included ✓ USB Type-A downstream ports quantity 3 Remote control included ✓ USB Type-C downstream ports quantity 3 Remote control included ✓ USB Type-C downstream ports quantity 1 Quick start guide ✓ USB Type-C downstream ports quantity 1 Quick start guide ✓ HDMI * ✓ Quick start guide ✓ ✓ HDMI version 1.4 Sustainability compliance ✓ ✓ DisplayPort version 1.4 Sustainability certificates ENERGY STAR, TCO ✓ DisplayPort version 1.4 Doesn't contain PVC/BFR ✓ Headphone out * ✓ ✓ ✓ ✓ Microphone in X | | Silver | Bezel width (bottom) | 8.95 mm |
| USB hub version3.2 Gen 2 (3.1 Gen 2)Stand includedXUSB upstream port typeUSB Type-CCables includedCp isplayPort, USB Type-A to USB Type-CNumber of USB Type-C upstream ports quantity1Power adapter includedUSB Type-A downstream ports quantityARemote control includedXUSB Type-C downstream ports quantityAStalus includedXUSB Type-C downstream ports quantityAStalus includedXUSB Type-C downstream ports quantityAOiley Port cable lengthAHDMI *ISustainability complianceIIHDMI version1.4Sustainability complianceINERGY STAR, TCODisplayPort version1.4Oesn't containPVC/BFRHeadphone out *IMercentrolMercentrolMicrophone inXAStatinability certificatesMercentrolPC Audio inXMercentrolMercentrolMercentrolPC Audio inXMercentrolMercentrolMercentrolMicrophone inXMercentrolMercentrolMercentrolPC Audio inXMercentrolMercentrolMercentrolMicrophone inXMercentrolMercentrolMercentrolMicrophone inXMercentrolMercentrolMercentrolMicrophone inXMercentrolMercentrolMercentrolMicrophone inXMercentrolMercentrolMercentrolMicrophone in | | | Packaging content | |
| USB hub version 3.2 Gen 2 (3.1 Gen 2) AC, DisplayPort, USB Type-A to USB Type-C USB upstream port type USB Type-C Type-C Number of USB Type-C upstream ports quantity 1 Power adapter included USB Type-A downstream ports quantity 3- Remote control included X USB Type-C downstream ports quantity 1 Kemote control included X USB Type-C downstream ports quantity 1 Quick start guide X USB Type-C downstream ports quantity 1 Income port (Start guide) X HDMI * Income port (Start guide) X X HDMI ports quantity 1 Sustainability compliance Income port (Start guide) HDMI version 1.4 Sustainability compliance INERGY STAR, TCO DisplayPort version 1.4 Doesn't contain PVC/BFR Headphone out * Income port (Start guide) Income port (Start guide) Income port (Start guide) Microphone in X X X X PC Audio in X Income port (Start guide) Income port (Start guide) | | | Stand included | × |
| DSB upsite am port type DSB Type-C Type-C Type-C Number of USB Type-C upstream ports quantity 1 Power adapter included USB Type-A downstream ports quantity 3 Remote control included X USB Type-C downstream ports quantity 1 Quick start guide X USB Type-C downstream ports quantity 1 Quick start guide X USB Type-C downstream ports quantity 1 Quick start guide X HDMI * V DisplayPort cable length 1.8 m HDMI ports quantity 1 Sustainability compliance HDMI version 1.4 Sustainability compliance DisplayPort version 1.4 Sustainability certificates ENERGY STAR, TCO DisplayPort version 1.4 Doesn't contain PVC/BFR Headphone out * Microphone in X Heavy metals free Hg (mercury) PC Audio in X Compliance certificates RoHS SHI | | | | |
| ports quantityIPower adapter includedIUSB Type-A downstream ports quantity3Remote control includedXUSB Type-C downstream ports quantity1Quick start guideXUSB Type-C downstream ports quantity1Quick start guideIHDMI*IDisplayPort cable length1.8 mHDMI version1.4Sustainability complianceIDisplayPorts quantity2Sustainability complianceENERGY STAR, TCODisplayPort version1.4Doesn't containPVC/BFRHeadphone out *IIIIMicrophone inXIIIPC Audio inXCompliance certificatesRendyPC Audio inXCompliance certificatesRendy | | USB Type-C | Cables included | |
| USB Type-A downstream ports quantityRemote control included×QuantityStylus included×USB Type-C downstream ports quantity1Quick start guide✓HDMI *✓DisplayPort cable length1.8 mHDMI ports quantity1Sustainability✓HDMI version1.4Sustainability compliance✓DisplayPort version1.4Sustainability certificatesENERGY STAR, TCODisplayPort version1.4Doesn't containPVC/BFRHeadphone out *✓Microphone in×Kanobility freeHaevy metals freeHg (mercury)PC Audio in×Compliance certificatesRoHS | | 1 | Power adapter included | ✓ |
| quantityStylus includedXUSB Type-C downstream ports quantity1Quick start guideHDMI *DisplayPort cable length1.8 mHDMI ports quantity1Sustainability1.8 mHDMI version1.4Sustainability complianceDisplayPorts quantity2Sustainability certificatesENERGY STAR, TCODisplayPort version1.4Doesn't containPVC/BFRHeadphone out *Other featuresMicrophone inXHeavy metals freeHg (mercury)PC Audio inXCompliance certificatesRoHS | | 2 | Remote control included | × |
| quantityIQuick start guide✓HDMI *✓DisplayPort cable length1.8 mHDMI ports quantity1SustainabilitySustainability complianceHDMI version1.4Sustainability compliance✓DisplayPorts quantity2Sustainability certificatesENERGY STAR, TCODisplayPort version1.4Doesn't containPVC/BFRHeadphone out *✓Other featuresFeaturesMicrophone inXHeavy metals freeHg (mercury)PC Audio inXCompliance certificatesRoHS | 1 2 | 3 | Stylus included | × |
| HDMI*Image: Margin point cable length1.8 mHDMI ports quantity1SustainabilityHDMI version1.4Sustainability complianceDisplayPorts quantity2Sustainability certificatesDisplayPort version1.4Doesn't containHeadphone out *Image: Margin point for the summary of the summar | | 1 | Quick start guide | Image: A set of the set of the |
| HDMI version1.4Sustainability compliance✓DisplayPorts quantity2Sustainability certificatesENERGY STAR, TCODisplayPort version1.4Doesn't containPVC/BFRHeadphone out *✓Other featuresMicrophone inMicrophone in×Heavy metals freeHg (mercury)PC Audio in×Compliance certificatesRoHS | | 1 | DisplayPort cable length | 1.8 m |
| DisplayPorts quantity 2 Sustainability certificates ENERGY STAR, TCO DisplayPort version 1.4 Doesn't contain PVC/BFR Headphone out * ✓ Other features ✓ Microphone in × Heavy metals free Hg (mercury) PC Audio in × Compliance certificates RoHS | HDMI ports quantity | 1 | Sustainability | |
| DisplayPorts quantity2Sustainability certificatesENERGY STAR, TCODisplayPort version1.4Doesn't containPVC/BFRHeadphone out *·Other featuresImage: State Sta | HDMI version | 1.4 | Sustainability compliance | 1 |
| DisplayPort version 1.4 Doesn't contain PVC/BFR Headphone out * ✓ Other features ✓ Microphone in × Heavy metals free Hg (mercury) PC Audio in × Compliance certificates RoHS | DisplayPorts quantity | 2 | | ENERGY STAR, TCO |
| Microphone in × Heavy metals free Hg (mercury) PC Audio in × Compliance certificates RoHS | DisplayPort version | 1.4 | | |
| Microphone in × Heavy metals free Hg (mercury) PC Audio in × Compliance certificates RoHS | Headphone out * | 1 | Other features | |
| PC Audio in X Compliance certificates RoHS | Microphone in | × | | Ha (mercury) |
| | PC Audio in | × | - | |
| | HDCP | 1 | P | - |



5397184821411

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.