

APC SMTL3000RMI2UC UPS-virtalähde Linjainteraktiivinen 3 kVA 2700 W 9 AC-pistorasia(a)

Tuotemerkki : APC Tuotekoodi: SMTL3000RMI2UC

Tuotteen nimi: SMTL3000RMI2UC



APC SMTL3000RMI2UC. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 3 kVA, Lähtöteho: 2700 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: C20 liitin, Ulostulojen määrä: 9 ACpistorasia(a). Akkuteknologia: Litiumioni (Li-Ion). Kotelo: Telineasennettava, Tuotteen väri: musta, Harmaa, Telineen kapasiteetti: 2U. Vaatimustenmukaisuustodistukset: RoHS



	Design	
Line-Interactive 3 kVA 2700 W Sine 160 V 286 V 50/60 Hz 220 V 240 V 50/60 Hz 739 J 6 ms 3:1 ✓ 55 dB	Rack capacity Product colour * Control type Display type LED indicators International Protection (IP) code Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Compliance certificates	2U Black, Grey Touch LCD ✓ IP20 0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3048 m 0 - 7620 m RoHS
,	Rack mount kit	/
C13 coupler, C19 coupler C20 coupler 9 AC outlet(s) 1 1	Sustainability Sustainability compliance Weight & dimensions Width Depth Height	RJ-45, USB cable 432 mm 683 mm 86 mm
	3 kVA 2700 W Sine 160 V 286 V 50/60 Hz 220 V 240 V 50/60 Hz 739 J 6 ms 3:1 C13 coupler, C19 coupler C20 coupler 9 AC outlet(s) 1 1	Line-Interactive 3 kVA 2700 W Control type Sine 160 V 286 V International Protection (IP) code 50/60 Hz 220 V 240 V 50/60 Hz 739 J 6 ms 3:1 V 55 dB Certificates Compliance certificates Packaging content Rack mount kit Cables included Cables included Cables included Sustainability Sustainability Sustainability Suith Pepth Height Weight & dimensions Width Depth Height

Battery		Packaging data	
Battery technology	Lithium-Ion (Li-Ion)	Package width	600 mm
Hot-swap battery	✓	Package depth	980 mm
Automatic battery test	✓	Package height	458 mm
Design		Package weight	41.5 kg
J		Other features	
Form factor *	Rackmount	Nominal output voltage	230 V
		Nominal input voltage	230 V





731304643173

0731304643173

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.