



## DELL PowerEdge R660XS server 480 GB Rack (1U) Intel Xeon Silver 4410T 2.7 GHz 32 GB DDR5-SDRAM 700 W

**Brand :** DELL

**Product family:** PowerEdge

**Product code:** 9VV4D

**Product name :** R660XS



- No OS

- Intel Xeon Silver 4410T (26.25MB Cache, 2.7GHz)

- 32GB DDR5-SDRAM (1 x 32) & 480GB SSD

- iDRAC9, Enterprise 16G

Intel Xeon Silver 4410T (26.25MB Cache, 2.7GHz), 32GB DDR5-SDRAM, 480GB SSD, LAN (Broadcom 5720), PERC H755, iDRAC9, Enterprise 16G, 2 x 700W, No OS

[DELL PowerEdge R660XS server 480 GB Rack \(1U\) Intel Xeon Silver 4410T 2.7 GHz 32 GB DDR5-SDRAM 700 W:](#)

### The perfect blend of performance and density

Run the most popular IT applications easily with this air-cooled server that is the best choice for balanced and dense compute.

DELL PowerEdge R660XS. Processor family: Intel Xeon Silver, Processor frequency: 2.7 GHz, Processor model: 4410T. Internal memory: 32 GB, Internal memory type: DDR5-SDRAM, Memory layout (slots x size): 1 x 32 GB. Total storage capacity: 480 GB. Ethernet LAN, Cabling technology: 10/100/1000Base-T(X). Power supply: 700 W, Redundant power supply (RPS) support. Chassis type: Rack (1U)



Processor		Ports & interfaces	
Processor manufacturer *	Intel	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
Processor family *	Intel Xeon Silver	<b>Design</b>	
Processor model *	4410T	Chassis type *	Rack (1U)
Processor frequency *	2.7 GHz	Product colour	Black
Processor boost frequency	4 GHz	Rack rails	✓
Processor cores	10	Bezel	✓
Processor cache	26.25 MB	<b>Performance</b>	
Number of processors installed	1	Remote administration	iDRAC9, Enterprise 16G
Maximum internal memory supported by processor	512 GB	Trusted Platform Module (TPM)	✓
<b>Memory</b>		Trusted Platform Module (TPM) version	2.0
Internal memory *	32 GB	<b>Software</b>	
Internal memory type *	DDR5-SDRAM	Operating system installed *	✗
Buffered memory type	Registered (buffered)	Compatible operating systems *	Canonical Ubuntu Server LTS Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware vSAN/ESXi
Memory ranking	2	<b>Power</b>	
Memory slots	16x DIMM	Redundant power supply (RPS) support *	✓
Memory layout (slots x size)	1 x 32 GB	Power supply *	700 W
Memory data transfer rate	5600 MT/s	Number of redundant power supplies supported	2
Maximum internal memory *	1 TB	Number of redundant power supplies installed	2
<b>Storage</b>		Power supply input voltage	200 - 240 V
Total storage capacity *	480 GB	Power cable length	2 m
Number of SSDs installed	1		
SSD capacity	480 GB		
SSD interface	SATA III		
SSD size	2.5"		
RAID support *	✓		
Supported RAID controllers	PERC H755		
Hot-Plug support	✓		

<b>Storage</b>		<b>Power</b>	
Internal drive bays	8	Power cable connector 1	C13 coupler
Supported storage drive interfaces	SAS, Serial ATA	Power cable connector 2	C14 coupler
<b>Graphics</b>		Power cable current	12 A
On-board graphics card	✘	<b>Operational conditions</b>	
<b>Network</b>		Operating temperature (T-T)	10 - 35 °C
LAN controller	Broadcom 5720	Storage temperature (T-T)	-40 - 65 °C
Ethernet LAN	✔	Storage relative humidity (H-H)	5 - 95%
Cabling technology	10/100/1000Base-T(X)	Operating altitude	0 - 3048 m
Ethernet interface type	Gigabit Ethernet	Non-operating altitude	0 - 12000 m
<b>Ports &amp; interfaces</b>		<b>Weight &amp; dimensions</b>	
Ethernet LAN (RJ-45) ports *	4	Width	434 mm
USB 2.0 ports quantity	2	Height	42.8 mm
		<b>Other features</b>	
		Data transfer rate	6 Gbit/s
		Bytes per sector	512



5397184843468

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-FEB-2025. Prints or copies of Information are only valid on the printed Publication date