



DELL PowerEdge R660XS server 480 GB Rack (1U) Intel Xeon Silver 4410T 2.7 GHz 32 GB DDR5-SDRAM 700 W

Brand : DELL

Product family: PowerEdge

Product code: 9VV4D

Product name : R660XS



- No OS

- Intel Xeon Silver 4410T (26.25MB Cache, 2.7GHz)

- 32GB DDR5-SDRAM (1 x 32) & 480GB SSD

- iDRAC9, Enterprise 16G

Intel Xeon Silver 4410T (26.25MB Cache, 2.7GHz), 32GB DDR5-SDRAM, 480GB SSD, LAN (Broadcom 5720), PERC H755, iDRAC9, Enterprise 16G, 2 x 700W, No OS

[DELL PowerEdge R660XS server 480 GB Rack \(1U\) Intel Xeon Silver 4410T 2.7 GHz 32 GB DDR5-SDRAM 700 W:](#)

The perfect blend of performance and density

Run the most popular IT applications easily with this air-cooled server that is the best choice for balanced and dense compute.

DELL PowerEdge R660XS. Processor family: Intel Xeon Silver, Processor frequency: 2.7 GHz, Processor model: 4410T. Internal memory: 32 GB, Internal memory type: DDR5-SDRAM, Memory layout (slots x size): 1 x 32 GB. Total storage capacity: 480 GB. Ethernet LAN, Cabling technology: 10/100/1000Base-T(X). Power supply: 700 W, Redundant power supply (RPS) support. Chassis type: Rack (1U)



Processor		Performance	
Processor manufacturer *	Intel	Remote administration	iDRAC9, Enterprise 16G
Processor family *	Intel Xeon Silver	Trusted Platform Module (TPM)	✓
Processor model *	4410T	Trusted Platform Module (TPM) version	2.0
Processor frequency *	2.7 GHz	Software	
Processor boost frequency	4 GHz	Operating system installed *	✗
Processor cores	10	Compatible operating systems *	
Processor cache	26.25 MB	Canonical Ubuntu Server LTS Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware vSAN/ESXi	
Number of processors installed	1	Power	
Maximum internal memory supported by processor	512 GB	Redundant power supply (RPS) support *	✓
Memory		Power supply *	700 W
Internal memory *	32 GB	Number of redundant power supplies supported	2
Internal memory type *	DDR5-SDRAM	Number of redundant power supplies installed	2
Buffered memory type	Registered (buffered)	Power supply input voltage	200 - 240 V
Memory ranking	2	Power cable length	2 m
Memory slots	16x DIMM	Power cable connector 1	C13 coupler
Memory layout (slots x size)	1 x 32 GB	Power cable connector 2	C14 coupler
Memory data transfer rate	5600 MT/s	Power cable current	12 A
Maximum internal memory *	1 TB	Operational conditions	
Storage		Operating temperature (T-T)	10 - 35 °C
Total storage capacity *	480 GB	Storage temperature (T-T)	-40 - 65 °C
Number of SSDs installed	1	Storage relative humidity (H-H)	5 - 95%
SSD capacity	480 GB	Operating altitude	0 - 3048 m
SSD interface	SATA III		
SSD size	2.5"		
RAID support *	✓		
Supported RAID controllers	PERC H755		
Hot-Plug support	✓		

Storage		Operational conditions	
Internal drive bays	8	Non-operating altitude	0 - 12000 m
Supported storage drive interfaces	SAS, Serial ATA	Carbon footprint	
Graphics		Total carbon footprint (kg of CO2e)	6561
On-board graphics card	✗	Total carbon emissions, standard deviation (kg of CO2e)	3677
Network		Carbon emissions, manufacturing (kg of CO2e)	459
LAN controller	Broadcom 5720	Carbon emissions, logistics (kg of CO2e)	131
Ethernet LAN	✓	Carbon emissions, energy usage (kg of CO2e)	5971
Cabling technology	10/100/1000Base-T(X)	Total carbon emissions, w/o use phase (kg of CO2e)	590
Ethernet interface type	Gigabit Ethernet	PAIA version	1.3.2, 2022
Ports & interfaces		Weight & dimensions	
Ethernet LAN (RJ-45) ports *	4	Width	434 mm
USB 2.0 ports quantity	2	Height	42.8 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	Other features	
Design		Data transfer rate	6 Gbit/s
Chassis type *	Rack (1U)	Bytes per sector	512
Product colour	Black		
Rack rails	✓		
Bezel	✓		



5397184843468

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.