



DELL PowerEdge R660XS palvelin 960 GB Teline (1U) Intel® Xeon® Gold 5416S 2 GHz 32 GB DDR5-SDRAM 1100 W

Tuotemerkki : DELL

Tuoteperhe: PowerEdge

Tuotekoodi: VJ454

Tuotteen nimi : R660XS



DELL PowerEdge R660XS. Suoritinperhe: Intel® Xeon® Gold, Prosessorin taajuus: 2 GHz, Prosessorimalli: 5416S. Sisäinen muisti: 32 GB, Sisäisen muistin tyyppi: DDR5-SDRAM, Muistin sijoittelu (paikat x koko): 1 x 32 GB. Kokonaistallennuskapasiteetti: 960 GB. Ethernet LAN, Kaapelitekniikka: 10/100/1000Base-T(X). Virtalähde: 1100 W, Vikasietoisen virtalähteen tuki (RPS). Alustatyyppi: Teline (1U)



Processor		Ports & interfaces	
Processor manufacturer *	Intel	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
Processor family *	Intel® Xeon® Gold	Design	
Processor model *	5416S	Chassis type *	Rack (1U)
Processor frequency *	2 GHz	Product colour	Black
Processor boost frequency	4 GHz	Rack rails	✓
Processor cores	16	Bezel	✓
Processor cache	30 MB	Performance	
Number of processors installed	1	Remote administration	iDRAC9, Enterprise 16G
Thermal Design Power (TDP)	150 W	Trusted Platform Module (TPM)	✓
Maximum internal memory supported by processor	512 GB	Trusted Platform Module (TPM) version	2.0
Memory		Software	
Internal memory *	32 GB	Operating system installed *	✗
Internal memory type *	DDR5-SDRAM	Compatible operating systems *	Canonical Ubuntu Server LTS Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware vSAN/ESXi
Buffered memory type	Registered (buffered)	Power	
Memory ranking	2	Redundant power supply (RPS) support *	✓
Memory slots	16x DIMM	Power supply *	1100 W
Memory layout (slots x size)	1 x 32 GB	Number of redundant power supplies supported	2
Memory data transfer rate	5600 MT/s	Number of redundant power supplies installed	2
Maximum internal memory *	1 TB	Power supply input voltage	100 - 240 V
Storage		Power cable length	2 m
Total storage capacity *	960 GB		
Number of SSDs installed	2		
SSD capacity	480 GB		
SSD interface	SATA III		
SSD size	2.5"		
RAID support *	✓		
Supported RAID controllers	PERC H755		

Storage		Power	
Hot-Plug support	✓	Power cable connector 1	C13 coupler
Internal drive bays	8	Power cable connector 2	C14 coupler
Supported storage drive interfaces	SAS, Serial ATA	Power cable current	12 A
Graphics		Operational conditions	
On-board graphics card	✗	Operating temperature (T-T)	10 - 35 °C
Network		Storage temperature (T-T)	-40 - 65 °C
LAN controller	Broadcom 5720	Storage relative humidity (H-H)	5 - 95%
Ethernet LAN	✓	Operating altitude	0 - 3048 m
Cabling technology	10/100/1000Base-T(X)	Non-operating altitude	0 - 12000 m
Ethernet interface type	Gigabit Ethernet	Weight & dimensions	
Ports & interfaces		Width	434 mm
Ethernet LAN (RJ-45) ports *	4	Height	42.8 mm
USB 2.0 ports quantity	2	Other features	
		Data transfer rate	6 Gbit/s
		Bytes per sector	512



5397184843475

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-FEB-2025. Prints or copies of Information are only valid on the printed Publication date