



Lenovo ThinkSystem ST650 V3 palvelin Tower Intel® Xeon Silver 4410Y 2 GHz 32 GB DDR5-SDRAM 1100 W



Tuotemerkki : Lenovo

Tuoteperhe: ThinkSystem

Tuotekoodi: 7D7AA00NEA

Tuotteen nimi : ST650 V3

Lenovo ThinkSystem ST650 V3. Suoritinperhe: Intel® Xeon Silver, Prosessorin taajuus: 2 GHz, Prosessorimalli: 4410Y. Sisäinen muisti: 32 GB, Sisäisen muistin tyyppi: DDR5-SDRAM, Muistin sijoittelu (paikat x koko): 1 x 32 GB. Ethernet LAN, Kaapelitekniikka: 10/100/1000Base-T(X). Virtalähde: 1100 W, Vikasietoisen virtalähteen tuki (RPS). Alustatyyppi: Tower

Processor		Performance	
Processor manufacturer *	Intel	Performance management	XClarity Controller Platinum
Processor family *	Intel Xeon Silver	Trusted Platform Module (TPM)	✓
Processor model *	4410Y	Trusted Platform Module (TPM) version	2.0
Processor frequency *	2 GHz	Software	
Processor boost frequency	3.9 GHz	Operating system installed *	✗
Processor cores	12	Microsoft Windows Server 2019 Microsoft Windows Server 2022 Red Hat Enterprise Linux 8.6 Red Hat Enterprise Linux 8.7 Red Hat Enterprise Linux 9.0 Red Hat Enterprise Linux 9.1 SUSE Linux Enterprise Server 15 SP4 SUSE Linux Enterprise Server 15 Xen SP4 Ubuntu 22.04 LTS 64-bit VMware ESXi 7.0 U3 VMware ESXi 8.0 U1	
Processor cache	30 MB	Compatible operating systems *	
Number of processors installed	1	Processor special features	
Configurable TDP-down	4.5 W	CPU configuration (max)	1
Bus type	OPI	Intel Smart Response Technology version	1.00
Memory		Intel Stable Image Platform Program (SIPP) version	0.00
Internal memory *	32 GB	Intel Secure Key Technology version	1.00
Internal memory type *	DDR5-SDRAM	Intel TSX-NI version	0.00
ECC	✓	Power	
Memory layout (slots x size)	1 x 32 GB	Redundant power supply (RPS) support *	✓
Maximum internal memory *	4 TB	Power supply *	1100 W
Storage		Number of redundant power supplies installed	1
Maximum storage capacity *	320 TB	Operational conditions	
RAID support *	✓	Operating temperature (T-T)	5 - 45 °C
RAID levels	0, 1, 10, JBOD	Storage temperature (T-T)	-40 - 60 °C
Supported RAID controllers	9350-8i	Operating relative humidity (H-H)	8 - 90%
Hot-swap	✓	Storage relative humidity (H-H)	8 - 90%
Internal drive bays	8	Operating altitude	0 - 3050 m
Network		Weight & dimensions	
LAN controller	Broadcom 57416	Width	175 mm
Ethernet LAN	✓	Depth	734 mm
Cabling technology	10/100/1000Base-T(X)	Height	462 mm
Ethernet interface type	10 Gigabit Ethernet	Weight	39.1 kg
Ports & interfaces			
Ethernet LAN (RJ-45) ports *	2		
USB 2.0 ports quantity	1		
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	5		
VGA (D-Sub) ports quantity	1		
Serial ports quantity	1		
Design			
Chassis type *	Tower		
Product colour	Black		
Redundant fans support	✓		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-FEB-2025. Prints or copies of Information are only valid on the printed Publication date