Lenovo ThinkSystem SR665 V3 palvelin Teline (2U) AMD EPYC 9124 3 GHz 32 GB DDR5-SDRAM 1100 W



Tuotemerkki : Lenovo

Tuoteperhe: ThinkSystem

Tuotekoodi: 7D9AA01TEA

Tuotteen nimi : SR665 V3

Lenovo ThinkSystem SR665 V3. Suoritinperhe: AMD EPYC, Prosessorin taajuus: 3 GHz, Prosessorimalli: 9124. Sisäinen muisti: 32 GB, Sisäisen muistin tyyppi: DDR5-SDRAM, Muistin sijoittelu (paikat x koko): 1 x 32 GB. Ethernet LAN, Kaapelitekniikka: 10/100/1000Base-T(X). Virtalähde: 1100 W, Vikasietoisen virtalähteen tuki (RPS). Alustatyyppi: Teline (2U)

| Processor | | Design | |
|---|---|---|--|
| Processor manufacturer * Processor family * Processor model * Processor frequency * Processor boost frequency Processor cores Processor cache Number of processors installed | AMD AMD EPYC 9124 3 GHz 3.7 GHz 16 64 MB 1 | Product colour Rack mounting | Black 🖌 |
| | | Performance | |
| | | Performance management Trusted Platform Module (TPM) Trusted Platform Module (TPM) version | XClarity Controller Platinum ✓ 2.0 |
| Memory | | Software | |
| Internal memory * Internal memory type * Memory clock speed Memory layout (slots x size) | 32 GB DDR5-SDRAM 4800 MHz 1 x 32 GB | Operating system installed * Compatible operating systems * | × Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi, Ubuntu Server |
| Storage | | Power | |
| Optical drive type * | × | Redundant power supply (RPS) support * | Image: A second s |
| Graphics | | Power supply * | 1100 W |
| Maximum graphics card memory | 16 MB | Number of redundant power supplies installed | 1 |
| Network | | Operational conditions | |
| Ethernet LAN Cabling technology Ethernet interface type Ports & interfaces | ✓ 10/100/1000Base-T(X) Gigabit Ethernet | Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) | 5 - 45 °C -40 - 60 °C 8 - 90% |
| Ethernet LAN (RI-45) ports * | 1 | Storage relative humidity (H-H) | 8 - 90% |
| USB 2.0 ports quantity | 1 | Operating altitude | 0 - 3050 m |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 4 | Weight & dimensions Width | 445 mm |
| VGA (D-Sub) ports quantity | 1 | Depth | 766 mm |
| Design | | Height | 87 mm |
| Chassis type * | Rack (2U) | | |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.