

iiyama XUB2492HSU-B6 tietokoneen litteä näyttö 60,5 cm (23.8") 1920 x 1080 pikseliä Full HD LED musta

Tuotemerkki : iiyama

Tuotekoodi: XUB2492HSU-B6

Tuotteen nimi : XUB2492HSU-B6

iiyama XUB2492HSU-B6. Näytön halkaisija: 60,5 cm (23.8"), Näytön erottelutarkkuus: 1920 x 1080 pikseliä, HD-tyyppi: Full HD, Näytön teknologia: LED, Vasteaika (tyypillinen): 0,4 ms, Vakiokuvasuhde: 16:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäiset kaiuttimet. Sisäänrakennettu USB-keskus. VESA-kiinnitys, Korkeudensäätö. Tuotteen väri: musta



Display		Ports & interfaces	
Display diagonal *	60.5 cm (23.8")	Headphone out *	✓
Display resolution *	1920 x 1080 pixels	HDCP	✓
HD type *	Full HD	Ergonomics	
Native aspect ratio *	16:9	VESA mounting *	✓
Display technology *	LED	Panel mounting interface	100 x 100 mm
Panel type *	IPS	Cable lock slot *	✓
Touchscreen *	✗	Height adjustment *	✓
Display brightness (typical)	250 cd/m ²	Adjustable height (max)	15 cm
Response time *	0.4 ms	Swivelling	✓
Screen shape *	Flat	Tilt adjustment	✓
Contrast ratio (typical) *	1300:1	Tilt angle range	5 - 22°
Maximum refresh rate *	100 Hz	Power	
Viewing angle, horizontal	178°	Energy efficiency class (SDR) *	D
Viewing angle, vertical	178°	Energy consumption (SDR) per 1000 hours *	13 kWh
Display number of colours *	16.7 million colours	Power consumption (typical) *	15 W
Pixel pitch	0.275 x 0.275 mm	Power consumption (standby) *	0.5 W
Horizontal scan range	30 - 115 kHz	Power consumption (off)	0.3 W
Display diagonal (metric)	60.5 cm	AC input voltage	100 - 240 V
Performance		AC input frequency	50/60 Hz
NVIDIA G-SYNC *	✗	Energy efficiency scale	A to G
AMD FreeSync *	✓	European Product Registry for Energy Labelling (EPREL) code	1671415
Flicker-free technology	✓	Weight & dimensions	
Low Blue Light technology	✓	Width (with stand)	539.5 mm
Multimedia		Depth (with stand)	209.5 mm
Number of speakers	2	Height (with stand)	493 mm
RMS rated power	2 W	Weight (with stand)	4.9 kg
Built-in speaker(s) *	✓		
Built-in camera *	✗		

Design		Weight & dimensions	
Product colour *	Black	Width (without stand)	539.5 mm
Ports & interfaces		Depth (without stand)	209.5 mm
Built-in USB hub *	✓	Height (without stand)	343 mm
HDMI *	✓	Packaging data	
HDMI ports quantity	1	Package width	609 mm
DisplayPorts quantity	1	Package depth	159 mm
DisplayPort version	1.4	Package height	398 mm



4948570122578

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-MAR-2025. Prints or copies of Information are only valid on the printed Publication date