

## Philips 5000 series 49B2U5900CH/00 LED display 124 cm (48.8") 5120 x 1440 pikseliä Dual QHD LCD musta



**Tuotemerkki :** Philips

**Tuoteperhe:** 5000 series

**Tuotekoodi:** 49B2U5900CH/00

**Tuotteen nimi :**  
49B2U5900CH/00

Curved Business Monitor 49B2U5900CH Kaareva 32:9 SuperWide -näyttö, jossa on USB-C

Philips 5000 series 49B2U5900CH/00 LED display 124 cm (48.8") 5120 x 1440 pikseliä Dual QHD LCD musta:

Tervetuloa tehokkaampaan työtilaan. Arjen työnsäilyä helpottava suuri 32:9 SuperWide -näyttö on varustettu uudella Varattu-valolla ja kallistettavalla web-kameralla, joiden ansiosta voit siirtyä tehtävästä toiseen vaivatta.

Philips 5000 series 49B2U5900CH/00. Näytön halkaisija: 124 cm (48.8"), Näytön erotelutarkkuus: 5120 x 1440 pikseliä, HD-tyyppi: Dual QHD, Näytön teknologia: LCD, Vasteaika (tyypillinen): 4 ms, Vakiokuvasuhde: 32:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäiset kaiuttimet. Sisäänrakennettu USB-keskus, USB-keskuksen versio: 3.2 Gen 1 (3.1 Gen 1). VESA-kiinnitys, Korkeudensäätö. Tuotteen väri: musta

Display		Network	
Display diagonal *	124 cm (48.8")	Ethernet LAN	✓
Display resolution *	5120 x 1440 pixels	<b>Ergonomics</b>	
HD type *	Dual QHD	VESA mounting *	✓
Native aspect ratio *	32:9	Panel mounting interface	100 x 100 mm
Display technology *	LCD	Cable lock slot *	✓
Panel type *	VA	Cable lock slot type	Kensington
Backlight type	W-LED	Height adjustment *	✓
Touchscreen *	✗	Adjustable height (max)	15 cm
Display brightness (typical)	450 cd/m <sup>2</sup>	Swivelling	✓
Response time *	4 ms	Swivel angle range	-30 - 30°
Anti-glare screen	✓	Tilt adjustment	✓
Screen shape *	Curved	Tilt angle range	-5 - 15°
Screen curvature rating	1800R	Picture-in-Picture	✓
Contrast ratio (typical) *	3000:1	On Screen Display (OSD)	✓
Contrast ratio (dynamic)	80000000:1	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Dynamic contrast ratio marketing name	SmartContrast	Number of OSD languages	21
Maximum refresh rate *	75 Hz	Plug and Play	✓
Viewing angle, horizontal	178°	LED indicators	Operation, Stand-by
Viewing angle, vertical	178°	<b>Power</b>	
Display number of colours *	1.07 billion colours	Energy efficiency class (SDR) *	F
Pixel pitch	0.2328 x 0.2328 mm	Energy efficiency class (HDR) *	G
Pixel density	109 ppi	Energy consumption (SDR) per 1000 hours *	43 kWh
Horizontal scan range	30 - 140 kHz	Energy consumption (HDR) per 1000 hours *	82 kWh
Vertical scan range	48 - 75 Hz	Power consumption (typical) *	46.1 W
Viewable size, horizontal	119.2 cm	Power consumption (standby) *	0.8 W
Viewable size, vertical	33.5 cm	Power consumption (PowerSave)	39 W
Display diagonal (metric)	124 cm	AC input voltage	100 - 240 V
High Dynamic Range (HDR) supported	✓	AC input frequency	50/60 Hz
High Dynamic Range (HDR) technology	DisplayHDR 400	Power supply type	Internal
DDC/CI	✓	Energy efficiency scale	A to G
Haze rate	25%		
Surface hardness	3H		
Colour depth	8 bit		
Colour gamut standard	sRGB		
sRGB coverage (typical)	119%		

<b>Display</b>		<b>Power</b>	
NTSC coverage (typical)	97%	European Product Registry for Energy Labelling (EPREL) code	1666129
Display sRGB	✓	<b>Operational conditions</b>	
<b>Performance</b>		Operating temperature (T-T)	0 - 40 °C
NVIDIA G-SYNC *	✗	Storage temperature (T-T)	-20 - 60 °C
AMD FreeSync *	✗	Operating relative humidity (H-H)	20 - 80%
Fast charging	✓	Operating altitude	0 - 3658 m
Fast charging technology	Power Delivery	Non-operating altitude	3658 - 12192 m
VESA Adaptive Sync support	✓	<b>Weight &amp; dimensions</b>	
Component video sync	Separate sync	Width (with stand)	1193 mm
Flicker-free technology	✓	Depth (with stand)	268 mm
Low Blue Light technology	✓	Height (with stand)	586 mm
<b>Multimedia</b>		Weight (with stand)	15.2 kg
Number of speakers	2	Width (without stand)	1193 mm
RMS rated power	6 W	Depth (without stand)	164 mm
Built-in speaker(s) *	✓	Height (without stand)	373 mm
Megapixel (approx.)	5 MP	Weight (without stand)	11.6 kg
Built-in microphone	✓	<b>Packaging data</b>	
Built-in camera *	✓	Package width	1290 mm
<b>Design</b>		Package depth	475 mm
Market positioning *	Business	Package height	300 mm
Product colour *	Black	Package weight	19.4 kg
Front bezel colour	Black	<b>Packaging content</b>	
Feet colour	Black	Stand included	✓
<b>Ports &amp; interfaces</b>		Cables included	AC, DisplayPort, HDMI, USB Type-C to USB Type-A, USB Type-C to USB Type-C
Built-in USB hub *	✓	Manual	✓
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Bundled software	SmartControl
USB upstream port type	USB Type-B, USB Type-C	<b>Sustainability</b>	
Number of upstream ports	2	Sustainability compliance	✓
Number of USB Type-B upstream ports quantity	1	Sustainability certificates	ENERGY STAR, EPEAT, TCO
Number of USB Type-C upstream ports quantity	1	Doesn't contain	Mercury, PVC/BFR
USB Type-A downstream ports quantity	2	<b>Other features</b>	
USB Type-C downstream ports quantity	1	HBR3 support	✓
USB Type-C DisplayPort Alternate Mode	✓	Compatible operating systems	Mac OS X Windows 11/10/8.1/8
USB Power Delivery (USB PD)	✓	Picture-by-Picture (PbP)	✓
USB Power Delivery up to	100 W	Exterior finish type	Textured
HDMI *	✓	Picture enhancement	SmartImage
HDMI ports quantity	2	Recyclable packaging material	100%
HDMI version	2.0	Regulatory Approvals	CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus
DisplayPorts quantity	1	Heavy metals free	Hg (mercury)
DisplayPort version	1.4	Delta E	2
Audio output	✓	EasyRead mode	✓
Microphone in	✓	LowBlue mode	✓
Built-in KVM switch	✓	Philips SmartUniformity	93 - 105%
HDCP	✓	Compliance certificates	CB, CE, Federal Communications Commission (FCC), RoHS, cTUVus
HDCP version	1.4/2.2	Mean time between failures (MTBF)	70000 h
		Ethernet LAN data rates	10,100,1000 Mbit/s
		Wake-on-LAN	✓
		<b>Recycling data</b>	
		Post-consumer recycled plastic	85%



8712581802578

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 06-MAR-2025. Prints or copies of Information are only valid on the printed Publication date