

QNAP TDS-h2489FU NAS Teline (2U) Intel® Xeon Silver 4314 512 GB DDR4 QuTS hero musta, Hopea

Tuotemerkki : QNAP

Tuotekoodi: TDS-H2489FU-4314-512G

Tuotteen nimi : TDS-h2489FU

QNAP TDS-h2489FU. Malli: NAS. Alustatyyppi: Teline (2U). Laitteen luokka: Suuryritys. Suoritinperhe: Intel® Xeon Silver, Prosessorimalli: 4314, Prosessorin taajuus: 2,4 GHz. Sisäinen muisti: 512 GB, Sisäisen muistin tyyppi: DDR4. Käyttöjärjestelmä asennettu: QuTS hero



Storage		Design	
Supported storage drive interfaces	M.2, Serial ATA, Serial ATA II, Serial ATA III, U.2	Product colour	Black, Silver
Storage drive sizes supported	2.5,M.2	Number of fans	6 fan(s)
Number of M.2 (M & B) slots	2	Fan diameter	6 cm
RAID support *	✓	LED indicators	Fan, Power, SSD, Status, Yes
RAID levels	0, 1, 5, 6, 10, 50, 60, JBOD	Built-in display	✓
Online RAID expansion	✓	Display type	OLED
RAID rebuild	✓	Performance	
Hot-swap drive bays	✓	Type *	NAS
Supported file systems	FAT32, HFS+, NTFS, exFAT, ext3, ext4	Device class *	Large Enterprise Business
Storage drives installed *	✗	Backup function *	✓
Number of storage drives supported *	24	Backup features	Cloud, iSCSI LUN
Installed storage drive type *	✗	Buzzer	✓
Supported storage drive types *	HDD & SSD	Multilingual support	✓
Auto-rebuild	✓	Snapshot	✓
Disk roaming	✓	Security algorithms	256-bit AES, AES, FIPS 140-2, SNMPv2, SNMPv3, TLS
Processor		Access Control List (ACL)	✓
Processor manufacturer *	Intel	Reset button	✓
Processor family *	Intel Xeon Silver	On/off switch	✓
Processor model *	4314	Built-in FTP server	✓
Processor frequency *	2.4 GHz	Browser supported	Apple Safari, Google Chrome, Microsoft Edge, Mozilla Firefox
Processor boost frequency	3.4 GHz	System log	✓
Processor cores	16	Hot spare	✓
Processor threads	32	S.M.A.R.T. support	✓
Processor cache	24 MB	Software	
Memory		Operating system installed *	QuTS hero
Internal memory *	512 GB	Operating system version	h5.0.0
Internal memory type	DDR4		
Maximum RAM supported	1 TB		
Memory slots	32		
Memory form factor	RDIMM		
ECC	✓		
Flash memory	5000 MB		

Network		Software	
Ethernet LAN *	✓		Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64
Ethernet LAN data rates	10,100,1000,2500,25000 Mbit/s		
DHCP server	✓		
Jumbo frames support	✓		
iSCSI support	✓		
Wake-on-LAN ready	✓		
Supported network protocols	IPv4, IPv6	Windows operating systems supported	
Dynamic DNS (DDNS)	✓		
Ports & interfaces			
USB port *	✓		
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4		
Fiber ports quantity	2		
Fiber optic connector	SFP28		
Ethernet LAN (RJ-45) ports *	4		
Concurrent connections	10000		
PCI Express x8 (Gen 4.x) slots	1		
PCI Express x16 (Gen 4.x) slots	1	Linux operating systems supported	CentOS 7.0, SuSE Linux 12.0, SuSE Linux 12.3, Ubuntu 14.04, Ubuntu 14.10, Ubuntu 15.04, Ubuntu 15.10, Ubuntu 16.04, Ubuntu 16.10, Ubuntu 17.10
Design			
Chassis type *	Rack (2U)		
Cooling type *	Active	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur
		Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
		Other operating systems supported	IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11
		Power	
		Power supply location	Built-in
		Power supply unit (PSU) capacity	1200 W
		Number of power supply units	2
		Power consumption (typical)	467.59 W
		AC input voltage	100 - 240 V
		Fan voltage	12 V
		Weight & dimensions	
		Width *	446.2 mm
		Depth *	713.2 mm
		Height *	88.3 mm
		Weight	21.3 kg
		Package weight	27.6 kg
		Packaging content	
		Cables included	AC, LAN (RJ-45)
		Power cables quantity	2
		Rack mount kit	✓
		Number of screws	98
		Drive tray key included	✓
		Operational conditions	
		Operating temperature (T-T)	0 - 35 °C
		Operating relative humidity (H-H)	5 - 95%
		Storage temperature (T-T)	-20 - 70 °C



4711103080474

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-DEC-2024. Prints or copies of Information are only valid on the printed Publication date