## **ATEN**

## ATEN CL5708IM-ATA-2XK06GG KVM-kytkin Telineasennus musta

Tuotemerkki: ATEN Tuotekoodi: CL5708IM-ATA-2XK06GG

Tuotteen nimi: CL5708IM-ATA-2XK06GG

ATEN CL5708IM-ATA-2XK06GG. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. Tietoturva-algoritmit: 128-bit RC4, RSA, SSL/TLS. HD-tyyppi: WUXGA, Enimmäiserottelutarkkuus: 1920 x 1200 pikseliä, Skannausväli: 1,255 s. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli, Muovi. Näyttö: LCD, Näytön halkaisija: 43,2 cm (17")





Ports & interfaces		Display	
Number of computers controlled * Keyboard port type * Mouse port type * Video port type *	8 USB, PS/2 USB, PS/2 VGA	Built-in display * Display Display diagonal On Screen Display (OSD)	✓ LCD 43.2 cm (17")
Console ports * Console USB ports quantity	RJ-45, USB A, VGA (D-Sub) 1	Power	
USB connector type	USB Type-A	Power source	AC
<b>Network</b> Ethernet LAN (RJ-45) ports	1	Input voltage AC input frequency Input current	100-240 V 50 - 60 Hz 1 A
Security algorithms	128-bit RC4, RSA, SSL/TLS	System requirements	
Performance  HD type *  Maximum resolution *  Scan interval	WUXGA solution * 1920 x 1200 pixels	Windows operating systems supported Linux operating systems supported Mac operating systems supported	* * *
DDC2B support	✓	Operational conditions	•
HDCP Hot-Plug support Daisy chain	* * *	Operational conditions  Operating temperature (T-T)  Storage temperature (T-T)  Operating relative humidity (H-H)	0 - 50 °C -20 - 60 °C 0 - 80%
Power on detection	<b>✓</b>	Weight & dimensions	
Firmware upgradeable  Design  Rack mounting *  Rack capacity	✓ 1U	Width Depth Height Weight	642.7 mm 480 mm 44 mm 13.5 kg
Product colour *	Black	Packaging content	
Housing material LED indicators Display switch button Push button	Metal, Plastic  ✓  ✓	Cables included Manual Rack mount kit	AC, KVM ✓
Hot keys Keyboard language	<b>✓</b> German		

