

ATEN CL6700MW-ATA-2XK06ITG KVM switch Rack mounting Black

Brand: ATEN Product code: CL6700MW-ATA-2XK06ITG

Product name: CL6700MW-ATA-2XK06ITG

USB DVI WideScreen Full HD LCD Console with USB, Italian

ATEN CL6700MW-ATA-2XK06ITG KVM switch Rack mounting Black:

The CL6700MW DVI Full HD LCD Console is a single rail KVM console featuring a 17.3" LED-backlit high-definition widescreen with an integrated keyboard and touchpad in a 1U rack-mountable sliding housing. The CL6700MW's console provides front end access to compatible KVM switches utilizing space with a module that closes fl at and slides into the rack. The single rail design allows the LCD monitor, keyboard and touchpad to operate independently of each other. Multiple video ports allow the console to connect one of three types of video sources: VGA, DVI, or HDMI - for the console and CPU connection. For added convenience, the full HD console provides two HDMI ports that allow for connecting a high-defi nition monitor to the console port, and/or an HDMI compatible switch to the KVM port.





Ports & interfaces		Power	
Number of computers controlled * Keyboard port type * Mouse port type * HDMI ports quantity DVI-D ports quantity VGA (D-Sub) ports quantity	USB USB 2 2 2	AC input frequency Input current Power consumption (typical)	50 - 60 Hz 1 A 19.4 W
		System requirements	
		Windows operating systems supported	/
USB connector type	USB Type-A, USB Type-B	Linux operating systems supported	✓
Performance		Mac operating systems supported	✓
HD type * Maximum resolution *	Full HD	Sustainability	
DDC/DDC2 supported	1920 x 1080 pixels	Compliance certificates	RoHS
DDC2B support	· ·	Operational conditions	
Design		Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -20 - 60 °C
Rack mounting *	/	Operating relative humidity (H-H)	0 - 80%
Rack capacity	duct colour * Black using material Metal D indicators	Weight & dimensions	
Housing material LED indicators Keyboard language		Width Depth Height Weight	589.2 mm 480 mm 44 mm 11.4 kg
Display		Packaging content	
Built-in display * Display	✓ LCD	Manual	•
Display diagonal	43.9 cm (17.3")	Logistics data	
Power		Harmonized System (HS) code	85176200
Input voltage	100 - 240 V		

