

ATEN CL5716M-ATA-2XK06ITG KVM-kytkin Telineasennus musta

Tuotemerkki: ATEN Tuotekoodi: CL5716M-ATA-2XK06ITG

Tuotteen nimi: CL5716M-ATA-2XK06ITG

ATEN CL5716M-ATA-2XK06ITG. Hiiriportin liitin: USB. Enimmäiserottelutarkkuus: 1280 x 1024 pikseliä, Skannausväli: 1,255 s. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli, Muovi. Näyttö: LCD, Näytön halkaisija: 43,2 cm (17"). Tulojännite: 100-240 V, AC-syöttötaajuus: 50 - 60

Hz, Syöttöjännite: 1 A



| Ports & interfaces | | Power | |
|---|------------------------------------|---|-------------------------------------|
| Number of computers controlled * Mouse port type * | 16 USB | AC input frequency Input current | 50 - 60 Hz 1 A |
| Performance | | Power consumption (typical) | 18 W |
| Maximum resolution * | 1280 x 1024 pixels | System requirements | |
| Scan interval DDC2B support | 1,255 s ✓ | Windows operating systems supported | ✓ |
| Hot-swap | | Linux operating systems supported | / |
| · | | Mac operating systems supported | / |
| Design | | Operational conditions | |
| Rack mounting * Rack capacity Product colour * Housing material | 1U Black Metal, Plastic | Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) | 0 - 40 °C -20 - 60 °C 0 - 80% |
| LED indicators | ✓ | Weight & dimensions | |
| Display Built-in display * ✓ Display LCD | Width Depth Height Weight | 642.7 mm 480 mm 44 mm 13.6 kg | |
| Display diagonal On Screen Display (OSD) | 43.2 cm (17") ✓ | Packaging content | |
| Power | | Manual | ✓ |
| Input voltage | 100-240 V | | |

