



ATEN KL1508AIM KVM-kytkin Telineasennus musta

Tuotemerkki : ATEN

Tuotekoodi: KL1508AIM-FR

Tuotteen nimi : KL1508AIM

ATEN KL1508AIM. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. HD-tyyppi: WUXGA, Enimmäiserottelutarkkuus: 1920 x 1200 pikseliä, Videokaistanleveys: 60 Hz. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelomateriaali: Metall. Näyttö: LCD, Näytön halkaisija: 43,2 cm (17"). Voimanlähde: AC, Tulojännite: 100 - 240 V, AC-syöttötaajuus: 50 - 60 Hz



| Ports & interfaces | | Display | |
|----------------------------------|--------------------------|-------------------------------------|---------------|
| Number of computers controlled * | 128 | Display diagonal | 43.2 cm (17") |
| Keyboard port type * | USB, PS/2 | On Screen Display (OSD) | ✓ |
| Mouse port type * | USB, PS/2 | Power | |
| Video port type * | VGA | Power source | AC |
| VGA (D-Sub) ports quantity | 1 | Input voltage | 100 - 240 V |
| Console ports * | PS/2, USB A, VGA (D-Sub) | AC input frequency | 50 - 60 Hz |
| Console USB ports quantity | 2 | Input current | 1 A |
| PS/2 ports quantity | 2 | Power consumption (typical) | 22.2 W |
| Network | | System requirements | |
| Ethernet LAN | ✓ | Windows operating systems supported | ✓ |
| Ethernet LAN (RJ-45) ports | 10 | Linux operating systems supported | ✓ |
| Performance | | Mac operating systems supported | ✓ |
| HD type * | WUXGA | Sustainability | |
| Maximum resolution * | 1920 x 1200 pixels | Compliance certificates | RoHS |
| Video bandwidth | 60 Hz | Operational conditions | |
| Scan interval | 1,255 s | Operating temperature (T-T) | 0 - 40 °C |
| Daisy chain | ✓ | Storage temperature (T-T) | -20 - 60 °C |
| Firmware upgradeable | ✓ | Operating relative humidity (H-H) | 0 - 80% |
| Design | | Weight & dimensions | |
| Rack mounting * | ✓ | Width | 480 mm |
| Rack capacity | 1U | Depth | 701.2 mm |
| Product colour * | Black | Height | 44 mm |
| Housing material | Metal | Weight | 15.2 kg |
| LED indicators | ✓ | Packaging content | |
| Push button | ✓ | Cables included | AC, KVM |
| Hot keys | ✓ | Manual | ✓ |
| Keyboard language | French | Rack mount kit | ✓ |
| Display | | | |
| Built-in display * | ✓ | | |
| Display | LCD | | |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-DEC-2024. Prints or copies of Information are only valid on the printed Publication date