## **ATEN**

## ATEN KL1116VN KVM-kytkin Telineasennus musta

Tuotemerkki: ATEN Tuotekoodi: KL1116VN-AXA-2XK06DNG

Tuotteen nimi: KL1116VN

ATEN KL1116VN. Näppäimistöportin liitin: USB, Hiiriportin liitin: USB, Videoportin tyyppi: DVI-D/VGA. Kaapelitekniikka: 10/100/1000Base-T(X). Enimmäiserottelutarkkuus: 1920 x 1200 pikseliä, Skannausväli: 1,255 s. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli. Näyttö: LCD, Näytön halkaisija: 48,3 cm (19")





| Ports & interfaces  |  | Design  |  |
|---|--|---|--|
| Number of computers controlled * Keyboard port type * Mouse port type * Video port type * DVI-D ports quantity VGA (D-Sub) ports quantity | 16 USB USB DVI-D/VGA 1 1 DVI-D, USB A, VGA (D-Sub) | Push button   | /                                      |
|   |  | Display   |  |
|   |  | Built-in display * Display Display diagonal On Screen Display (OSD)                     | ✓<br>LCD<br>48.3 cm (19")<br>✓         |
| Console USB ports quantity  | 2  | Power   |  |
| Network Ethernet LAN  | •  | Input voltage<br>AC input frequency   | 100-240 V<br>50 - 60 Hz                |
| Ethernet LAN (RJ-45) ports<br>Cabling technology  | 22<br>10/100/1000Base-T(X)                         | Sustainability Compliance certificates  | RoHS                                   |
| Performance   |  | Operational conditions  |  |
| Maximum resolution * Scan interval DDC2B support  | 1920 x 1200 pixels<br>1,255 s<br>✓                 | Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) | 0 - 40 °C<br>-20 - 60 °C<br>0 - 80%    |
| Design  |  | Weight & dimensions   |  |
| Rack mounting * Rack capacity Product colour * Housing material   | √<br>1U<br>Black<br>Metal                          | Width<br>Depth<br>Height<br>Weight  | 702.1 mm<br>480 mm<br>44 mm<br>15.3 kg |
| Cascadable  | ✓  | Packaging content   |  |
| LED indicators  | <b>✓</b>   | Cables included<br>Manual   | AC<br>✓                                |

