ATEN

ATEN KL1516AiM KVM-kytkin Telineasennus musta

Tuotemerkki : ATEN Tuotekoodi: KL1516AIM-AXA-2XK06GG

Tuotteen nimi: KL1516AiM

ATEN KL1516AiM. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. Enimmäiserottelutarkkuus: 1600 x 1200 pikseliä, Skannausväli: 1,255 s. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Näppäimistön kieli: Saksa. Näyttö: LCD, Näytön halkaisija: 43,2 cm (17"). Tulojännite: 100-240 V, AC-syöttötaajuus: 50 - 60 Hz, Virrankulutus: 30 W





Ports & interfaces		Display	
Number of computers controlled * Keyboard port type * Mouse port type * Video port type * VGA (D-Sub) ports quantity Console ports * Console USB ports quantity USB connector type	16 USB, PS/2 USB, PS/2 VGA 1 PS/2, USB A, VGA (D-Sub) 2 USB Type-A	Built-in display * Display Display diagonal On Screen Display (OSD)	LCD 43.2 cm (17")
		Power Input voltage AC input frequency	100-240 V 50 - 60 Hz
Network		Power consumption (typical)	30 W
Ethernet LAN	✓	System requirements	
Performance		Windows operating systems supported	✓
Maximum resolution * Automatic switching Scan interval DDC2B support	1600 x 1200 pixels 1,255 s	Sustainability Compliance certificates	RoHS
		Operational conditions	
Daisy chain Design		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C -20 - 60 °C 0 - 80%
Product colour * Bla LED indicators ✓	1U Black	Weight & dimensions	
		Width Depth Height Weight	701.2 mm 480 mm 44 mm 15.2 kg
		Packaging content	
		Manual	✓

