## **ATEN**

## ATEN KL1516AiM KVM switch Rack mounting Black

Brand: ATEN Product code: KL1516AIM-AXA-2XK06SG

Product name: KL1516AiM

16-Port Dual Rail LCD KVM Switch LCD Console + Cat 5 High-Density KVM Switch with KVM over IP ATEN KL1516AiM. Keyboard port type: USB, PS/2, Mouse port type: USB, PS/2, Video port type: VGA. Maximum resolution: 1600 x 1200 pixels, Scan interval: 1,255 s. Product colour: Black, Rack capacity: 1U, Keyboard language: Spanish. Display: LCD, Display diagonal: 43.2 cm (17"). Input voltage: 100-240 V, AC input frequency: 50 - 60 Hz, Power consumption (typical): 30 W





Ports & interfaces		Display	
Number of computers controlled * Keyboard port type * Mouse port type * Video port type * VGA (D-Sub) ports quantity Console ports * Console USB ports quantity USB connector type	16 USB, PS/2 USB, PS/2 VGA 1 PS/2, USB A, VGA (D-Sub) 2 USB Type-A	Built-in display * Display Display diagonal On Screen Display (OSD)	✓ LCD 43.2 cm (17") ✓
		Power	
		Input voltage AC input frequency Power consumption (typical)	100-240 V 50 - 60 Hz 30 W
Network		, ,,,,	30 W
Ethernet LAN	✓	System requirements	
Performance		Windows operating systems supported	✓
Maximum resolution * Automatic switching Scan interval DDC2B support	1600 x 1200 pixels  1,255 s	Sustainability	
		Compliance certificates	RoHS
		Operational conditions	
Daisy chain		Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -20 - 60 °C
Design		Operating relative humidity (H-H)	0 - 80%
Rack mounting * Rack capacity Product colour * LED indicators Keyboard language	✓ 1U Black ✓ Spanish	Weight & dimensions	
		Width Depth Height Weight	701.2 mm 480 mm 44 mm 15.2 kg
		Packaging content	
		Manual	✓

