## **ATEN**

## ATEN KL1516AN KVM-kytkin Telineasennus musta

Tuotemerkki : ATEN Tuotekoodi: KL1516AN-IT

Tuotteen nimi: KL1516AN

ATEN KL1516AN. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. HD-tyyppi: WUXGA, Enimmäiserottelutarkkuus: 1920 x 1200 pikseliä, Videokaistanleveys: 60 Hz. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli. Näyttö: LCD, Näytön halkaisija: 48,3 cm (19"). Voimanlähde: AC, Tulojännite: 100 - 240 V, AC-syöttötaajuus: 50 - 60 Hz





Ports & interfaces		Display	
Number of computers controlled * Keyboard port type * Mouse port type * Video port type *	USB, PS/2 USB, PS/2 VGA	Display Display diagonal On Screen Display (OSD)	LCD 48.3 cm (19") ✓
		Power	
VGA (D-Sub) ports quantity Console ports * Console USB ports quantity PS/2 ports quantity  Network	1 PS/2, USB A, VGA (D-Sub) 2 2	Power source Input voltage AC input frequency Input current Power consumption (typical)	AC 100 - 240 V 50 - 60 Hz 1 A 22.1 W
Ethernet LAN	✓	System requirements	
Ethernet LAN (RJ-45) ports  Performance	16	Windows operating systems supported	/
HD type *	WUXGA	Linux operating systems supported	<b>✓</b>
Maximum resolution *	1920 x 1200 pixels	Mac operating systems supported	✓
Video bandwidth	60 Hz	Sustainability	
Scan interval	1,255 s	Compliance certificates	RoHS
Daisy chain Firmware upgradeable	1	Operational conditions	
Design		Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -20 - 60 °C
Rack mounting *	111	Operating relative humidity (H-H)	0 - 80%
Rack capacity  Product colour *	1U Black	Weight & dimensions	
Housing material LED indicators	Metal	Width Depth Height	480 mm 701.2 mm 44 mm
Push button Hot keys	<b>V</b>	Packaging content	
Keyboard language	Italian	Cables included	AC, KVM
Display		Manual	✓
Built-in display *	✓	Rack mount kit	✓

