ATEN

ATEN KL1516AN KVM-kytkin Telineasennus musta

Tuotemerkki : ATEN Tuotekoodi: KL1516AN-US

Tuotteen nimi: KL1516AN

ATEN KL1516AN. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. HD-tyyppi: WUXGA, Enimmäiserottelutarkkuus: 1920 x 1200 pikseliä, Videokaistanleveys: 60 Hz. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli. Näyttö: LCD, Näytön halkaisija: 48,3 cm (19"). Voimanlähde: AC, Tulojännite: 100 - 240 V, AC-syöttötaajuus: 50 - 60 Hz





Ports & interfaces		Display	
Number of computers controlled * Keyboard port type * Mouse port type * Video port type *	ard port type * USB, PS/2 port type * USB, PS/2 port type * VGA D-Sub) ports quantity 1 e ports * PS/2, USB A, VGA (D-Sub) e USB ports quantity 2	Display diagonal	48.3 cm (19")
		On Screen Display (OSD)	✓
		Power	
VGA (D-Sub) ports quantity Console ports * Console USB ports quantity PS/2 ports quantity		Power source Input voltage AC input frequency Input current	AC 100 - 240 V 50 - 60 Hz 1 A
Network		Power consumption (typical)	22.1 W
Ethernet LAN	✓	System requirements	
Ethernet LAN (RJ-45) ports	16	Windows operating systems supported	✓
Performance		Linux operating systems supported	✓
HD type * Maximum resolution * Video bandwidth Scan interval	WUXGA 1920 x 1200 pixels 60 Hz 1,255 s	Mac operating systems supported	✓
		Sustainability	
		Compliance certificates	RoHS
Plug and Play	√	Operational conditions	
Firmware upgradeable	✓	Operating temperature (T-T)	0 - 40 °C
Design		Storage temperature (T-T) Operating relative humidity (H-H)	-20 - 60 °C 0 - 80%
Rack mounting *	1U Black Metal	Weight & dimensions	
Product colour * Black Housing material Metal LED indicators ✓		Width Depth Height Weight	480 mm 701.2 mm 44 mm 15.4 kg
Push button Hot keys	v .	Packaging content	
Keyboard language	US English	Cables included	AC, KVM
Display		Manual	✓
Built-in display *		Rack mount kit	✓
Display	✓ LCD		
Display	LCD		

