ATEN

ATEN KL1516AN KVM-kytkin Telineasennus musta

Tuotemerkki : ATEN Tuotekoodi: KL1516AN-CH

Tuotteen nimi: KL1516AN

ATEN KL1516AN. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2, Videoportin tyyppi: VGA. HD-tyyppi: WUXGA, Enimmäiserottelutarkkuus: 1920 x 1200 pikseliä, Videokaistanleveys: 60 Hz. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli. Näyttö: LCD, Näytön halkaisija: 48,3 cm (19"). Voimanlähde: AC, Tulojännite: 100 - 240 V, AC-syöttötaajuus: 50 - 60 Hz





Ports & interfaces		Display	
Number of computers controlled * Keyboard port type * Mouse port type * Video port type * VGA (D-Sub) ports quantity	512 USB, PS/2 USB, PS/2 VGA 1	Display diagonal	48.3 cm (19")
		On Screen Display (OSD)	✓
		Power	
		Power source Input voltage	AC 100 - 240 V
Console ports *	PS/2, USB A, VGA (D-Sub)	AC input frequency	50 - 60 Hz
Console USB ports quantity PS/2 ports quantity	2	Input current	1 A
	2	Power consumption (typical)	22.1 W
Network		System requirements	
Ethernet LAN (RJ-45) ports	16	Windows operating systems supported	v
Performance		Linux operating systems supported	✓
HD type * Maximum resolution * Video bandwidth Scan interval	WUXGA 1920 x 1200 pixels 60 Hz 1,255 s	Mac operating systems supported	✓
		Sustainability	
		Compliance certificates	RoHS
Daisy chain	✓	Operational conditions	
Firmware upgradeable	✓	Operating temperature (T-T)	0 - 40 °C
Design		Storage temperature (T-T)	-20 - 60 °C
Rack mounting *	✓	Operating relative humidity (H-H)	0 - 80%
Rack capacity	1U	Weight & dimensions	
Product colour *	Black	Width	480 mm
Housing material	Metal	Depth	701.2 mm
LED indicators	✓	Height	44 mm
Push button	<i>y</i>	Weight	15.4 kg
Hot keys		Packaging content	
Keyboard language	Swiss	Cables included	AC, KVM
Display		Manual	✓
Built-in display *	✓	Rack mount kit	×
Display	LCD		

