

## SilverNet MAX 240-PCP Network bridge 240 Mbit/s White

**Brand :** SilverNet

**Product code:** SIL MAX 240-PCP

**Product name :** MAX 240-PCP



- Point-to-Point Outdoor Wireless Bridge Up to 20KM
- Point-to-MultiPoint Client
- 240Mbps throughput
- Integrated Dual 25dBi Antenna
- Designed for Outdoor applications
- SNMP
- AES Encryption up to 256bit
- MIMO with spatial multiplexing
- DFS (Dynamic Frequency Selection)
- TPC (transmit Power Control)
- PoE 802.3af
- Upgradable to 500Mbps

240Mbps, 25dBi, PoE, MIMO, DFS, 1G LAN, 370x370x90 mm, pre-configured SilverNet MAX 240-PCP. Maximum data transfer rate: 240 Mbit/s, Maximum transfer distance: 60000 m, Supported data transfer rates: 95, 240, 500Mbps. Antenna design: Internal, Antenna gain level (max): 23 dBi, Pan/tilt-axis range: 180°. Wi-Fi band: Single-band (5 GHz), Top Wi-Fi standard: Wi-Fi 5 (802.11ac), WLAN data transfer rate (max): 1300 Mbit/s. Ethernet LAN interface type: Gigabit Ethernet, Ethernet LAN data rates: 10,100,1000 Mbit/s, Networking standards: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11i, IEEE 802.11n, IEEE 802.1Q, IEEE 802.1x. Connectivity technology: Wired & Wireless

Data transmission		Features	
Maximum data transfer rate *	240 Mbit/s	Surge protection	✓
Maximum transfer distance	60000 m	Quality of Service (QoS) support	✓
Supported data transfer rates	95, 240, 500Mbps	Wi-Fi Multimedia (WMM)/(WME)	✓
Antenna		Network Time Protocol (NTP) client	✓
Antenna design	Internal	Mean time between failures (MTBF)	60000 h
Antenna gain level (max)	23 dBi	System requirements	
Pan/tilt-axis range	180°	Minimum system requirements	Internet Explorer, Google Chrome, Mozilla Firefox
Antennas quantity	1	Compatible operating systems	Microsoft Windows, Mac OS, Linux Distributions
Wireless LAN features		Power	
Wi-Fi	✓	Power source type	DC, PoE
Wi-Fi band	Single-band (5 GHz)	AC input voltage	100-240 V
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)	Power supply	15.4 W
WLAN data transfer rate (max)	1300 Mbit/s	DC input voltage	24-48/48-56 V
Frequency band	5.1 - 5.8 GHz	Power consumption (typical)	6 W
Transmission gain	0 - 23 dB	Power consumption (max)	16 W
Signal strength	-40 dBm	Power over Ethernet (PoE)	✓
Channels quantity	25 channels	Power over Ethernet (PoE) voltage	48 V
Modulation	16-QAM, 64-QAM, 256-QAM, BPSK, QPSK	Power plug type	Type G
Receiver sensitivity	-82dBm@54Mbps, -74dBm@300Mbps, -68dBm@1.3Gbps	Operational conditions	
Output power (dBm)	26	Operating temperature (T-T)	-20 - 70 °C
Indoor range	60000m	Operating temperature (T-T)	-4 - 158 °F
Outdoor range	60000m	Operating relative humidity (H-H)	0 - 95%
Network		Storage temperature (T-T)	-40 - 90 °C
Ethernet LAN	✓	Storage relative humidity (H-H)	0 - 95%
Ethernet LAN interface type	Gigabit Ethernet	Certificates	
Ethernet LAN data rates	10,100,1000 Mbit/s	Certification	CE, FCC
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11i, IEEE 802.11n, IEEE 802.1Q, IEEE 802.1x	Weight & dimensions	
		Antenna diameter	51 cm

<b>Network</b>		<b>Weight &amp; dimensions</b>	
Cabling technology	10/100/1000Base-T(X)	Width	370 mm
Full duplex	✓	Depth	370 mm
Auto MDI/MDI-X	✓	Height	90 mm
Static IP	✓	Weight	2.5 kg
Dynamic IP	✓	<b>Packaging content</b>	
<b>Ports &amp; interfaces</b>		Packaging content	Includes 2 x radios, 2 x PoE injector PSU's and 2 x Tilt and Swivel 3 Axis mounting brackets.
Connectivity technology	Wired & Wireless	PoE+ Injector(s)	✓
Ethernet LAN (RJ-45) ports	1	Mounting bracket(s) included	✓
<b>Security</b>		Power supply included	✓
Security algorithms	256-bit AES, 802.1x RADIUS, SNMPv2, SSH	Antenna included	✓
MAC address filtering	✓	Quick installation guide	✓
Authentication method	WPA2 AES	<b>Packaging data</b>	
<b>Management features</b>		Package width	305 mm
Management protocols	SNMP V2	Package depth	445 mm
Web-based management	✓	Package height	460 mm
DHCP client	✓	Package weight	9.37 kg
<b>Features</b>		Package type	Box
Product type *	Network bridge	Quantity per pack	2 pc(s)
Product colour	White	<b>Logistics data</b>	
Remote control function	✓	UK Trade Tariff code	85176200
LED indicators	LAN, Signal strength	Country of origin	United Kingdom
Automatic Transmit Power Control (ATPC)	✓		
Wall mountable	✓		
Reset button	✓		
International Protection (IP) code	IP67		



5060693980138

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-DEC-2024. Prints or copies of Information are only valid on the printed Publication date