SilverNet TDD605-PCP Network bridge 500 Mbit/s White

Brand : SilverNet Product code: SIL TDD605-PCP

Product name: TDD605-PCP

- Interference Free Ethernet connectivity
- Point-to-Point up to 500m
- Up to 500Mbps throughput
- Designed for outdoor applications with rugged case design
- Small Form Factor
- 16 QAM to 64 QAM Modulations
- Gigabit Ethernet
- Power over Ethernet (PoE)
- WEB Management
- IP67 Rated
- Easy installation

500Mbps, 3x RJ-45, 60 GHz, IP67, PoE+, 36 dBi, 165x165x100 mm

SilverNet TDD605-PCP. Maximum data transfer rate: 500 Mbit/s, Maximum transfer distance: 500 m. Antenna design: Internal, Antenna gain level (max): 36 dBi. Frequency band: 59 - 66GHz, Modulation: 16-QAM, 64-QAM, QPSK. Ethernet LAN interface type: Gigabit Ethernet, Ethernet LAN data rates: 1000 Mbit/s, Networking standards: IEEE 802.1D, IEEE 802.1p, IEEE 802.3at. Security algorithms: 128-bit AES, 256-bit AES, SNMPv2, SNMPv3



Data transmission		Features	
Maximum data transfer rate *	500 Mbit/s	International Protection (IP) code	IP67
Maximum transfer distance	500 m	Power	
Antenna		Power over Ethernet (PoE)	✓
Antenna design	Internal	Operational conditions	
Antenna gain level (max)	36 dBi	Operating temperature (T-T)	-45 - 55 °C
Wireless LAN features		Certificates	
Frequency band	59 - 66GHz	continuates	FCC 15.255, ETSI EN 302 217-3 &
Modulation	16-QAM, 64-QAM, QPSK	Certification	UK IR 2078 & IR 2000, EMC, USA FCC 47CFR 15 & ETSI EN 301 489, UL/EN 60950
Network			
Ethernet LAN	✓	Weight & dimensions	
Ethernet LAN interface type	Gigabit Ethernet	Width	165 mm
Ethernet LAN data rates	1000 Mbit/s	Depth	165 mm
Networking standards	IEEE 802.1D, IEEE 802.1p, IEEE 802.3at	Height	100 mm
Static IP	1	Weight	1.8 kg
Ports & interfaces		Packaging content	
Ethernet LAN (RJ-45) ports	3	Grounding	✓
Security		PoE+ Injector(s)	✓
Security	rithms 128-bit AES, 256-bit AES, SNMPv2, SNMPv3	Mounting bracket(s) included	1
Security algorithms		Power supply included	✓
Management features		Antenna included	✓
Web-based management	✓	Quick installation guide	✓
Features		Packaging data	
Product type *	Network bridge	Quantity per pack	1 pc(s)
Mounting type	Pole/Wall	Logistics data	
Product colour	White	UK Trade Tariff code	85176200
Power LED	✓		
Wall mountable	✓		



5060693980817

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.